



Main

Range	Spacial
Accessory / separate part category	Locking accessory
Product or component type	Handle
Application	Multi-purpose
Mounting support	Direct mounting on standard lock
Product compatibility	S3D enclosure
Range compatibility	Spacial Spacial S3D
Device composition	1 cylindrical barrel 2 key 1 handle with key lock

Complementary

Quantity per set	Set of 1
Material	Handle: PA + TES Key lock: zamak + steel Cylindrical barrel: zamak + PA (polyamide)
Lock type	Key lock
Type of keylock	Cylindrical
Key number	1242
Net weight	0.051 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	7.0 cm
Package 1 Length	10.0 cm
Package 1 Weight	51.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	250
Package 2 Height	40.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	13.842 kg
Unit Type of Package 3	PAM
Number of Units in Package 3	2500
Package 3 Height	93.0 cm
Package 3 Width	100.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	151.42 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------