

FEATURES

- Quality 316L grade stainless steel wire rope
- Available in 75m rolls
- Contamination are not acceptable
- Food processing equipment
- Laboratory systems

RS PRO Stainless Steel Wire Rope, 75m

RS Stock No.: 183-5857



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

The Wire Rope history reaches the 19th century, which means it is well-known and in everyday use by many professionals worldwide. The Steel Wire Rope consists of several strands of metal twisted together. When the strands are closed over a central core, we are dealing with producing a rope. It provides a sturdy means for lifting and lowering loads reliably and safely. Several different sizes of Wires offer support to users in terms of maximum corrosion protection and excellent resistance to abrasion. Wire Cables provide flexibility for many construction projects that are essential to run your business. We are proudly introducing our own branded RS PRO Stainless Wire Rope with an impressive working load of 300 kg. These wires and ropes are not suitable for general lifting use as the primary intention are to secure and support applications. For lifting slings and chains, see a range of Straps, Slings and Chains within this section. Our Steel Wires have their recognition in demanding conditions and conform to all RoHS compliant.

General Specifications

Туре	Wire Rope
Material	Stainless Steel
Number of Strands	6
Number Of Wires	7
Core	Wire Core
SWL at 5:1 Factor of Safety	26kg
Applications	Paper Mills, Food processing equipment, Laboratory systems, Boat fittings (e.g. to solve any manner of rigging issues), Mining sector (screening), Medical implants, Brewery equipment

Mechanical Specifications

Length	75m
Diameter	5mm
Grip Size	6mm
Safe Working Load	300kg
Torque	3.5 N/mm

Wire Rope



Approvals

Safety Standard	ISO BS EN 12385-4:2002, RoHS Regulations
-----------------	--