

RS Part Number: **773-7989**

Specifications and dimensions



- Rotary Isolator For Din Rail Mount
- Complete With Shaft and Handle
- Din Rail Mount Switch

| Dimensions: | |
|--|--------------------|
| Height | 87 mm |
| Width | 139 mm |
| Depth | 56 mm |
| Handle: | |
| Height | 64 mm |
| Width | 139 mm |
| Depth | 42 mm |
| Shaft: | |
| Length | 282 mm |
| Weight | 0.677 Kg |
| Features | |
| Rated operational voltage Ue IEC &EN | 690 V |
| Rated operational voltage Ue UL | 600 V |
| Rated impulse withstand voltage Uimp | 6 kV |
| Rated uninterrupted current Iu | 63 A |
| Rated operational current Ie AC22A | 63 A |
| Rated operational current Ie AC21A | 80 A |
| Rated operational current Ie AC1 | 80 A |
| Rated operational power AC23A (50/60Hz) 230V | 30 kW |
| Rated operational power AC23A (50/60Hz) 415V | 37 kW |
| Rated operational power AC23A (50/60Hz) 690V | 45 kW |
| Rated operational power AC3 (50/60Hz) 230V | 22 kW |
| Rated operational power AC3 (50/60Hz) 415V | 22 kW |
| Rated operational power AC3 (50/60Hz) 690V | 30 kW |
| UL power rating 3 phase DOL 110V | 7.5 hp |
| UL power rating 3 phase DOL 230V | 15 hp |
| UL power rating 3 phase DOL 480V | 25 hp |
| UL power rating 3 phase DOL 600V | 30 hp |
| UL power rating 1 phase DOL 110V | 3 hp |
| UL power rating 1 phase DOL 230V | 7.5 hp |
| UL short circuit fuse rating class J | 70 A |
| UL rated fused short circuit current | 10 kA |
| IEC short circuit capacity max fuse size GI | 63 A |
| IEC rated fused short circuit current | 30 kA |
| Maximum terminal capacity | 25 mm ² |
| Recommended tightening torque | 2 Nm |
| Related Products | |
| Neutral contact early make/late break | 136-5280 |
| Main pole contact | 136-5281 |
| Gasket to provide IP65 rating | 773-7995 |