

FEATURES

- UL approved Nylon 66, 94V-2, With good tensile strength and insulation, not easy to get aging.
- Color: Yellow, other special colors are available upon request.
- Use to bundle wires, cables, wrapping and get gardening neat and tidy.
- Easy to thread.

RS PRO Cable Ties

RS Stock No.: 2243133



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description ATTRIBUTE 1

- Material: UL approved Nylon 66, 94V-2, With good tensile strength and insulation, not easy to get aging.
- Color: Yellow, other special colors are available upon request.
- · Feature: Use to bundle wires, cables, wrapping and get gardening neat and tidy.
- · Insert tie into the lock of head and pull out easily to bundle it.

General Specifications

| Series | |
|-------------------------------|--------------------|
| Туре | Non-Releasable |
| Colour | Yellow |
| Material | Nylon 66 |
| Finish | |
| Application | |
| Resistant To | |
| UV Resistant | No |
| Minimum Operating Temperature | -40°C |
| Maximum Operating Temperature | 85°C |
| Fire Behaviour | Self-Extinguishing |
| Quantity | 100 |

Mechanical Specifications

| Length | 203mm(8") |
|------------------|-------------|
| Width | 4.6mm |
| Tensile Strength | 50lbs/22kgs |
| Max. Bundle Dia. | 52mm |
| Thickness | 1.5±0.25mm |



Protection Category

IP Rating

Classification

| eCI@ss (10.0.1) | |
|-----------------|--|
| UNSPSC (6.01) | |

Approvals

| Declarations | |
|---------------|---|
| Standards Met | UL, RoHS, SVHC, DNV.GL, Lloyd's, CE, VDE, ABS, HF |

Similar Products

| Stock No. | Brand | Product Name | Colour | Material | Tensile strength |
|-----------|--------|------------------|--------|----------|---------------------|
| 233-229 | RS PRO | Yellow cable tie | Yellow | Nylon 66 | 18lbs/8kg |
| 233-269 | RS PRO | Yellow cable tie | Yellow | Nylon 66 | 18lbs/8kg |















