Product data sheet Characteristics

KB31_1_AS_G2

Vivace 16AX 250V 1 Gang 1 Way Switched, Aluminium silver



Main		
Range	Vivace	
Product or component type	Switch	
Device short name	KB31	
Device application	Control	
Switch function	1-way	

Complementary

Device presentation	Complete mechanism
Actuator	Rocker
Number of gangs	1 gang
Colour tint	Aluminium silver
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	16 AX at 250 V AC, inductive 16 AX at 250 V AC, fluorescent
[Ue] rated operational voltage	250 V AC
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	L1 L2 COM
Tightening torque	0.4 N.m
Clamping connection capacity	2.5 mm²
Width	87 mm
Height	87 mm

Environment

Standards	SS 227 MS IEC 60669-1 IEC 60669-1	
Ambient air temperature for operation	-540 °C	
Relative humidity	095 %	
Environmental characteristic	Indoor use	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.8 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	63 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	576 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	31.5 cm
Package 3 Length	50 cm
Package 3 Weight	5.37 kg

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₽¥Yes	