

Datasheet

RS Polyamide Terminal Blocks

SPECIFICATIONS

INSERTS:	BRASS
HOUSING:	POLYAMIDE (PA66)
TEMPERATURE	105°C
SCREWS:	GALVANISED STEEL
STANDARDS:	CE (BS EN 60998)
COLOUR:	NATURAL
FEATURES:	WITH WIRE PROTECTOR SEMI-RIGID & LOW COST FLAME RETARDANT HIGH TEMPERATURE ALL SCREWS ARE CAPTIVE & RAISED FOR EASY WIRING



RS Stock No.	CROSS SECTION	CURRENT RANGE	RATED VOLTAGE	DIMENSIONS (mm)							
				L	W	φ1	φ2	D	d	H	h
813-3120	4 mm ²	3 - 24 A	380 V	93	16.8	2.8	2.3	7.8	6	13.6	7.6
813-3123	6 mm ²	5 - 32 A	380 V	114	18.8	3.3	2.6	10	8	15	8.8
813-3127	10 mm ²	10 - 57 A	400 V	125	20.7	4.3	2.8	11	9	16.2	9.6
813-3136	12 mm ²	15 - 61 A	400 V	137	22.5	4.5	2.8	12	10	18.8	10.2
813-3139	16 mm ²	30 - 76 A	400 V	165	25.5	5.5	3	14	11	19.8	11.2
867-0988	25 mm ²	60 - 101 A	400 V	187	31.2	6.5	3.8	16.5	13	25.5	14.8

Cross-section rated for rigid wire and cables (if for flexible wire, it should be reduced one-step, i.e., 6mm² is 4mm²)

φ1 = wire entry hole diameter

φ2 = fixing hole diameter