



MASTERColour CDM-T

MASTERC CDM-T 250W/830 G12 1CT/12

Range of single-ended, compact, high-efficiency, discharge lamps with a stable color over lifetime and a crisp, sparkling light

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- Lamps may use electronic or electromagnetic control gear, except 35W/942 and 20W lamps, which must use electronic control gear.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Luminous Efficacy (rated) (Nom)	
Cap-Base	G12 [G12]		111 lm/W
Operating Position	UNIVERSAL [Any or Universal (U)]	Color rendering index (CRI)	85
Flux measurement reference	Sphere	Arc Length O (Nom)	12.3 mm
Life to 50% Failures (Nom)	15,000 hour(s)	Operating and Electrical	
Light Technical		Power Consumption	250.0 W
Color Code	830 [CCT of 3000K]	Voltage (Nom)	95 V
Luminous Flux	27,750 lm	Voltage (Nom)	95 V
Color Designation	Warm White (WW)	Controls and Dimming	
Chromaticity Coordinate X (Nom)	0.434	Dimmable	No
Chromaticity Coordinate Y (Nom)	0.398		
Correlated Color Temperature (Nom)	3000 K		

MASTERC colour CDM-T

Mechanical and Housing

Bulb Finish	Clear
Bulb Shape	T24 [T 24mm]

Approval and Application


Energy Efficiency Class	F
Mercury (Hg) Content (Max)	27.5 mg
Mercury (Hg) Content (Nom)	27.5 mg
Energy Consumption kWh/1000 h	250 kWh
EPREL Registration Number	473350

Product Data

Order product name	MASTERC CDM-T 250W/830 G12 1CT/12
--------------------	-----------------------------------



Full product name	MASTERC CDM-T 250W/830 G12 1CT/12
Full product code	871150020801915
Order code	928089805131
Material Nr. (12NC)	928089805131
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500208019
Numerator - Packs per outer box	12
EAN/UPC - Case	8711500208026

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)
MASTERC CDM-T 250W/830 G12 1CT/12	25 mm	12.3 mm	71.5 mm	73.5 mm	72.5 mm	135 mm

Photometric data




Light Distribution Diagram - MASTERC CDM-T 250W/830 G12 1CT/12

Spectral Power Distribution Colour - MASTERC CDM-T 250W/830 G12 1CT/12

MASTERC colour CDM-T

Lifetime



Lumen Maintenance Diagram - MASTERC CDM-T 250W/830 G12 1CT/12

Life Expectancy Diagram - MASTERC CDM-T 250W/830 G12 1CT/12

