



HUSQVARNA 525RX

Powerful yet lightweight and comfortable brushcutter. Tough on grass and undergrowth, easy on you.



Offset handle bar

Angled handlebar and comfort handles provides excellent grip and working position.



X-Torq® engine

The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.

Intuitive controls

The choke and purge are easy to reach and understand.



Balance 35

Ergonomic harness that distribute the load optimally between your shoulders, chest and back.



FEATURES

- Intuitive controls
- X-Torq® engine cuts emission and fuel consumption
- Offset handle bar for best comfort
- Balance 35 ergonomic harness
- Air purge for easier cold starting
- Auto return stop switch for easy starting

Technical specifications	
DIMENSIONS	
Tube diameter	24 mm
Tube length	1483 mm
Weight (excl. cutting equipment)	4.9 kg
ENGINE	
Clutch engagement speed (± 120)	4000 rpm
Cylinder bore	34 mm
Cylinder displacement	25.4 cm ³
Cylinder stroke	28 mm
Electrode gap	0.65 mm
Fuel consumption	600 g/kWh
Fuel tank volume	0.51 l
Idling speed	3000 rpm
Ignition module air gap	0.3 mm
Maximum power speed	8500 rpm
Maximum rpm output shaft	6500 rpm
Power output	1 kW
Spark plug	NGK BPMR8Y
Torque, max.	1.2 Nm
Torque, max. at rpm	6000 rpm
EQUIPMENT	
OEM Grass blade	Grass 255-4
OEM Harness	Balance 35
OEM Trimmer head	T35 M10
LUBRICANT	
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	106 dB(A)
Sound power level, measured	104 dB(A)
Sound pressure level at operators ear	93 dB(A)
TRANSMISSION	
Drive gear angle	30°
Gear ratio	19
VIBRATION	
Equivalent vibration level (ahv, eq) front handle	2.1 m/s ²
Equivalent vibration level (ahv, eq) rear handle	2.3 m/s ²
Exhaust emissions (CO average)	87.57 g/kWh
Exhaust emissions (NOx average)	0.56 g/kWh

PXM_SPAREPARTS



PURGE BUBBLE
503 93 66-01



FUEL FILTER FOR MOST OF OUR
HANDHELD PRODUCTS 503 79 88-01
503 44 32-01



504 11 50-01