# Product data sheet Characteristics

# E8331L2LED\_WG\_G2

Switch, AvatarOn, 1-pole 2-way, LED, brass terminal, IP20, wine gold





Main			
Product or component type	Switch		
Device application	Control		
Load type	Resistive Incandescent lamp Fluorescent lamp Inductive		
Colour tint	Wine gold		

Complementary

Device presentation	Complete product
Rated current	16 AX at 250 V AC 50/60 Hz
Switch function	1-pole 2-way
Number of gangs	1 gang
Number of rocker	1
Clamping connection capacity	3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s) 4 x 1.5 mm² for stranded cable(s)
Connections - terminals	Brass terminal
Local signalling	Off: LED indicator, LED
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator
Device mounting	Surface Flush
Width	86 mm
Height	86 mm
Depth	34.2 mm
Embedding depth	24.5 mm

#### Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	35 °C
Operating altitude	2000 m
Relative humidity	095 %
Standards	GB 16915.1 IS 3854

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.4 cm	
Package 1 Width	8.6 cm	
Package 1 Length	8.6 cm	
Package 1 Weight	81.0 g	

### Offer Sustainability

Green Premium product	
☑ REACh Declaration	
Yes	
Compliant EPEU RoHS Declaration	
Yes	
Yes	
China RoHS Declaration	
€Yes	
Product Environmental Profile	
No need of specific recycling operations	
	© REACh Declaration  Yes  Compliant © EU RoHS Declaration  Yes  Yes  Yes  China RoHS Declaration  © Yes  Product Environmental Profile