

FEATURES

- Versatile solder wire that is suitable for a wide range of soldering tasks
- Typical temperature of soldering iron tip for use with this solder is 360-400°C
- Melting point is 217-219°C
- Flux content 3.3%

RS PRO 1.27mm Wire Lead Free Solder, +217°C Melting Point

RS Stock No.: 756-8913



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

From the trusted RS PRO brand, this solder wire is a resin-based, SAC305 lead free solder wire that utilises a synthetically refined resin and effective activator package. The flux formulation of this solder wire is ideal for wetting common Printed Circuit Boards (PCBs) and any components as it leaves behind a clear residue that can be easily removed with dry brushing for a cleaner look or safely left on the PCB after soldering.

General Specifications

Product Form	Wire
Melting Point	217°C to 219°C
Percent Silver	3%
Percent Tin	96.5%
Flux Type	Rosin Based
Flux Content Percent	2.2 %
Percent Copper	0.5%
Applications	In securing electrical components to integrated circuit boards, moulded to secure components in place in solder joints, can also be used for light brazing, in repair, prototyping and production

Mechanical Specifications

Wire Diameter	1.27mm
Product Weight	250g

Operation Environment Specifications

Soldering Iron Tip Temperature	360°C to 400°C
---------------------------------------	----------------

Approvals

Standards Met	J-STD 004; J-STD 006
---------------	----------------------

