



Instruction Data sheet

ENGLISH

PROCESS CONTROL UNIT

Stock Number: 2228148



48 x 48 DIN Size Universal Input PID Process Controller

- 4 digits process (PV) and 4 digits process set value (SV) display
- Universal process input (TC, RTD, mV \equiv , V \equiv , mA \equiv)
- Dual or multi point calibration for \equiv voltage /current inputs
- Configurable ON/OFF, P, PI, PD ve PID control forms

- Adaptation of PID coefficients to the system with Auto-tune and Self-tune
- Manual/Automatic mode selection for control outputs
- Bumpless transfer
- Programmable heating, cooling and alarm functions for control outputs



Specifications

Input

Universal Input TC, RTD, Voltage / Current

Thermocouple (TC): L(DIN 43710) J, K, R, S, T, B, E, and N (IEC 584.1) (ITS90), C (ITS90)

Thermoresistance (RTD): PT-100 (IEC751) (ITS90)

Voltage/ Current Input Types Selectable by parameters.

0...50mV, 0...5V, 0...10V or 0...20mA, 4...20mA

Output

Standard Relay Outputs :3 pieces 5A@250V \sim at resistive load)

They can be programmed as Control or Alarm output) (Electrical Life 100000 operation Full Load)

Environmental Rating and Physical Specification

Operating Temperature : 0...50°C

Humidity : 0-90%RH (none condensing)

Protection Class: (IP65 at front, IP20 at rear).

Supply Voltage

100-240V \sim 50/60 Hz (-%15;+%10) -6VA

Dimensions

48 x 48 mm

Electrical Wirings

