

WP 11-115 Quick (603621000) Angle grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 603621000
EAN 4061792176287



Product may differ from Image



- Low fatigue as never before: compact angle grinder with smallest handle circumference in its class for perfect ergonomics
- Longer service life, more power: the Metabo Marathon-motor with patented dust protection, up to 20% more overload capacity and 50% more torque
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Tool-free adjustable guard; twist-proof
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated non-slip switch
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

Technical data**Characteristics**

| | |
|--------|-------------------|
| Disc-Ø | 115 mm // 4 1/2 " |
|--------|-------------------|

| | |
|-------------------|--------|
| Rated input power | 1100 W |
|-------------------|--------|

| | |
|--------------|-------|
| Output power | 700 W |
|--------------|-------|

| | |
|---------------|-----------|
| No-load speed | 11000 rpm |
|---------------|-----------|

| | |
|---------------------|----------|
| Speed at rated load | 7500 rpm |
|---------------------|----------|

| | |
|--------|----------------------|
| Torque | 3.2 Nm / 28.3 in-lbs |
|--------|----------------------|

| | |
|----------------|------|
| Spindle thread | M 14 |
|----------------|------|

| | |
|----------------------|------------------|
| Handle circumference | 195 mm / 7.688 " |
|----------------------|------------------|

| | |
|------------------------------|------------------|
| Weight (without power cable) | 2.3 kg / 5.1 lbs |
|------------------------------|------------------|

| | |
|--------------|-------------|
| Cable length | 4 m / 13 ft |
|--------------|-------------|

Vibration

| | |
|------------------|----------------------|
| Surface grinding | 4.8 m/s ² |
|------------------|----------------------|

| | |
|------------------------------|----------------------|
| Uncertainty of measurement K | 1.5 m/s ² |
|------------------------------|----------------------|

| | |
|-------------------------|----------------------|
| Grinding with sandpaper | 2.6 m/s ² |
|-------------------------|----------------------|

| | |
|------------------------------|----------------------|
| Uncertainty of measurement K | 1.5 m/s ² |
|------------------------------|----------------------|

Noise emission

| | |
|----------------------|----------|
| Sound pressure level | 93 dB(A) |
|----------------------|----------|

| | |
|-------------------------|-----------|
| Sound power level (LWA) | 104 dB(A) |
|-------------------------|-----------|

| | |
|------------------------------|---------|
| Uncertainty of measurement K | 3 dB(A) |
|------------------------------|---------|

Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Inner support flange

M-Quick flange nut