

**! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product WEICONLOCK AN 302-80
Code-Nr. 302800

**1.2. Relevant identified uses of the substance or mixture and uses advised against
Recommended intended purpose(s)**

1-Component Adhesives and Sealants, anaerobic curing

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

! SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315	
Eye Dam. 1	H318	
Skin Sens. 1	H317	
STOT SE 3	H335	
Aquatic Chronic 4	H413	

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

- H335 May cause respiratory irritation.
 H413 May cause long lasting harmful effects to aquatic life.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS05



GHS07

! Signal word

Danger

Hazard Statements

- H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H413 May cause long lasting harmful effects to aquatic life.

Precautionary Statements

- P102 Keep out of reach of children.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash hands thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/eye protection.
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P332 + P313 If skin irritation occurs: Get medical advice/attention.
 P362 Take off contaminated clothing.
 P363 Wash contaminated clothing before reuse.
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/container to hazardous or special waste collection point.

! Hazardous ingredients for labeling

acrylic acid, BISPHENOL A ETHOXYLATE DIMETHACRYLATE, cumene hydroperoxide

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**! SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

3.2. Mixtures**Description**

Anaerobic adhesive / sealant

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
79-10-7	201-177-9	acrylic acid	1 - 5	Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Acute Tox. 4, H312 / Acute Tox. 4, H302 / Skin Corr. 1A, H314 / Aquatic Acute 1, H400
80-15-9	201-254-7	cumene hydroperoxide	1 - 2,5	Org. Perox. E, H242 / Acute Tox. 3, H331 / Acute Tox. 4, H312 / Acute Tox. 4, H302 / STOT RE 2, H373 / Skin Corr. 1B, H314 / Aquatic Chronic 2, H411
107-21-1	203-473-3	ethanediol	< 1	Acute Tox. 4, H302 / STOT RE 2, H373
41637-38-1	609-946-4	BISPHENOL A ETHOXYLATE DIMETHACRYLATE	60 - 100	Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Eye Irrit. 2, H319 / STOT SE 3, H335 / Aquatic Chronic 4, H413

REACH

CAS No	Name	REACH registration number
79-10-7	acrylic acid	01-2119452449-31
80-15-9	cumene hydroperoxide	01-2119475796-19
107-21-1	ethanediol	01-2119456816-28
41637-38-1	BISPHENOL A ETHOXYLATE DIMETHACRYLATE	01-2119980659-17

Additional advice

CAS: 80-15-9: STOT SE3; H335: 1% < C < 10%

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

If swallowed give water to drink.

4.2. Most important symptoms and effects, both acute and delayed**Physician's information / possible symptoms**

Allergic symptoms

Confusion

skin irritation



Physician's information / possible dangers

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Dry fire-extinguishing substance

Carbon dioxide

sand

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO₂)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8



SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

Do not store together with reducing agents.

Do not store together with metals.

Further information on storage conditions

Store at +5 till +25 °C.

Protect from heat and direct solar radiation.

Store container at cool and aired place.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters

! Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
107-21-1	Ethane-1,2-diol: particulate	8 hours	10		EH40/2005
107-21-1	Ethane-1,2-diol: vapour	8 hours	52	20	EH40/2005
		Short-term	104	40	

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
107-21-1	ethanediol	8 hours	52	20	skin
		Short-term	104	40	

DNEL-/PNEC-values

DNEL worker

CAS No	Substance name	Value	Code	Remark
80-15-9	cumene hydroperoxide	6 mg/m ³	DNEL long-term inhalative (systemic)	

**! Additional advice**

The statutory local and national regulations have to be observed.

8.2. Exposure controls**Respiratory protection**

In case of insufficient ventilation or long-term effect use breathing apparatus.

Breathing apparatus in the event of aerosol or mist formation.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: fluorinated rubber; 0,7mm; 480min; 60min;

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

! SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

liquid

Colour

green

Odour

hardly noticeable

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not determined				
melting point	not determined				
Flash point	> 100 °C				
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	not determined				
Upper explosion limit	not determined				



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 04.01.2019 (GB) Version 8.6

WEICONLOCK AN 302-80

	Value	Temperature	at	Method	Remark
Vapour pressure	not determined				
Relative density	1,1 g/ml				
Vapour density	not determined				
Solubility in water		20 °C			easy soluble
Solubility/other			Organic solvent		teilweise mischbar
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity	ca. 4000 mPa*s	25 °C			

Oxidising properties

No information available.

Explosive properties

No information available.

9.2. Other information

No information available.

! SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reactions with strong oxidising agents.

Reactions with reducing agents.

Reactions with Metals.

10.4. Conditions to avoid

Metal, Metal-Salts

Keep away from heat.

10.5. Incompatible materials**Substances to avoid**

Oxidising agent, strong

Reducing agent, strong

Metal, Metal-Salts

10.6. Hazardous decomposition products

Gases/vapours, toxic

Carbon monoxide and carbon dioxide.

**Thermal decomposition**

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LD50 acute oral	1405 mg/kg	rat		CAS: 79-10-7
LD50 acute dermal	2000 mg/kg	rabbit		CAS: 79-10-7
LC50 acute inhalation	3,6 mg/l ()	rat		CAS: 79-10-7
Skin irritation	irritant			
Eye irritation	risk of strong eye injuries			
Skin sensitization	sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

! Experiences made from practice

May irritate the mucosae.
Sensitization through skin contact possible.
Risk of strong eye injuries.

Additional information

The product is to be handled with the caution usual with chemicals.
Other hazardous properties may not be excluded.
The product has not been tested. The information is derived from products of similar composition.

! SECTION 12: Ecological information**12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	LC50 3,9 mg/l (96 h)	Oncorhynchus mykiss		CAS: 80-15-9



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 04.01.2019 (GB) Version 8.6

WEICONLOCK AN 302-80

	Value	Species	Method	Validation
Daphnia	EC50 95 mg/l (48 h)	Daphnia magna		CAS: 79-10-7
Algae	EC50 0,04 mg/l (72 h)	Desmodesmus subspicatus.		CAS: 79-10-7
Bacteria	EC20 900 mg/l (30 min)	activated sludge		CAS: 79-10-7

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Biological degradability	CAS: 41637-38-1			Biodegradable
Degradability	CAS: 80-15-9			readily degradable

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

! SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

08 04 09*

Name of waste

waste adhesives and sealants containing organic solvents or other hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

! General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	-	-	-
14.6. Special precautions for user	No information available.		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	not applicable		
Transport/further information	No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.		

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content	ca.5 %
VOC value	45 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.5

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 04.01.2019 (GB) Version 8.6

WEICONLOCK AN 302-80

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.