



## Overview

|              |  |
|--------------|--|
| Presentation | This Series of Rack Power Distribution Units (PDU) comes with Locking IEC Receptacles. The output and input connections are C13 to C14. The cord length is 1.2m. Locking IEC system allows the use of optional locking IEC power cords for added power cord security and enhanced reliability. No tools are required to disengage the locking feature and remove the plug from the locking receptacle. |
| Lead time    | Usually in Stock   |

## Main

|                       |               |
|-----------------------|---------------|
| Input Connection Type | IEC 60320 C14 |
| Cable length          | 1.22 m        |
| Number of cables      | 6             |

## Physical

|                     |                    |
|---------------------|--------------------|
| Colour              | Black              |
| Height              | 24 cm              |
| Width               | 7 cm               |
| Depth               | 4.5 cm             |
| Net weight          | 1.01 kg            |
| Mounting preference | No preference      |
| Mounting mode       | Not rack-mountable |

## Input

|                      |      |
|----------------------|------|
| Max line current     | 10 A |
| Input current limits | 10 A |

## Output

|                                |                 |
|--------------------------------|-----------------|
| Max current draw               | 10 A            |
| Number of power socket outlets | 1 IEC 60320 C13 |
| Power cable length             | 1.22 m          |

## Conformance

|                        |                           |
|------------------------|---------------------------|
| Product certifications | CCC[RETURN]PSE[RETURN]VDE |
|------------------------|---------------------------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environmental

|                                       |                   |
|---------------------------------------|-------------------|
| Ambient air temperature for operation | 0...70 °C         |
| Relative humidity                     | 20...80 %         |
| Operating altitude                    | 0...10000 ft      |
| Ambient air temperature for storage   | -25...75 °C       |
| Storage Relative Humidity             | 20...80 %         |
| Storage altitude                      | 0.00...15240.00 m |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 24 cm   |
| Package 1 Width              | 4.5 cm  |
| Package 1 Length             | 7 cm    |
| Package 1 Weight             | 1.01 kg |

## Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Green Premium product   |
| REACH Regulation         | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive        | Compliant <a href="#">EU RoHS Declaration</a>   |
| Lead free                | Yes   |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile      | <a href="#">End Of Life Information</a>   |
| WEEE                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Take-back                | Take-back program available   |

## Contractual warranty

|          |                           |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|