

Condensate Drains

Features

- Precise self-activated control of fluids and air to a specified programme
- Automatically opens for a set time to drain condensation
- Minimal risk of internal blockages due to increased internal tolerances
- LED indicator for operational status
- Test facility for manual override

RS PRO R 3/8 Automatic Condensate Drain

RS Stock No.: 725-125



RS PRO is the own brand of RS. The RS PRO Seal of Approval is your assurance of professional quality, a guarantee that every part is rigorously tested, inspected, and audited against demanding standards. Making RS PRO the Smart Choice for our customers.

Condensate Drains

Product Description

This RS fully programmable drain valves is designed to provide automatic draining of filter bowls, separators, receivers etc. The automatic drain is effective at removing condensate and contaminants with the interval time for draining or discharge being pre-set to meet the requirements of your installation.

General Specifications

Drain Type	Automatic
Opening Duration	Set between 0.5 to 45 minutes
Frequency	Multi

Mechanical Specifications

Outlet Port	R 3/8
Inlet Port:	R 3/8
Body Material	Brass
Seal Material	Nitrile Rubber
Height	123mm
Width	96mm
Minimum Operating Pressure	0 bar
Maximum Operating Pressure	16 bar

Electrical Specifications

Supply Voltage	240V 50-60Hz
operational status	LED indicator

Condensate Drains

Protection Category

IP Rating	IP65
-----------	------

Classification

UNSPSC (Version)	40141605
------------------	----------

Approvals

Declarations	EN 61340-5-1:2007
--------------	-------------------