



## Main

Range of product	Easy Harmony XA2
Product or component type	Contact block
Device short name	ZA2E

## Complementary

Contact operation	Slow-break
Contact block type	Single
Contacts usage	Standard contacts
Positive opening	Without
Mechanical durability	1500000 cycles
Connections - terminals	, <= 2 x 1.5 mm <sup>2</sup> conforming to IEC 60947-1 , <= 1 x 2.5 mm <sup>2</sup> conforming to IEC 60947-1 , >= 1 x 0.5 mm <sup>2</sup> conforming to IEC 60947-1 Faston terminals, connection size: 6.3 mm conforming to IEC 60947-1
Tightening torque	0.8 N.m
Contacts material	Silver alloy (Ag/Ni)
Short-circuit protection	10 A fuse type gL conforming to IEC 60269-1
[Ith] conventional free air thermal current	10 A conforming to IEC 60947-5-1
[Ui] rated insulation voltage	600 V (pollution degree 3) conforming to IEC 60947-1
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-1
[Ie] rated operational current	2 A at 230 V, AC-15, A600 conforming to IEC 60947-5-1 0.2 A at 110 V, DC-13, Q600 conforming to IEC 60947-5-1
Electrical durability	500000 Cycles, AC-15, 2 A at 230 V, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 500000 cycles, DC-13, 0.2 A at 110 V, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1
Contacts type and composition	1 NC

## Environment

Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
Standards	IEC 60947-1 IEC 60529 IEC 60947-5-4 IEC 60947-5-1
Product certifications	CCC[RETURN]CE
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...55 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.520 cm
Package 1 Width	10.160 cm
Package 1 Length	10.160 cm
Package 1 Weight	20.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	5.200 cm
Package 2 Width	19.100 cm
Package 2 Length	17.000 cm
Package 2 Weight	100.000 g
Unit Type of Package 3	S02
Number of Units in Package 3	200
Package 3 Height	15.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	4.000 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>