



Main

Range	Pieno
Product or component type	Switch
Switch application	Switch
Load type	Resistive Fluorescent
Cover frame colour tint	White

Complementary

Device mounting	Flush Surface
Wiring device mounting	Surface Flush
Switch function	1-way
Rated current	16 AX at 250 V AC 50 Hz
Local signalling	Fluorescent (white)
Number of gangs	3 gangs
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 1.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s)
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	23 mm

Environment

Ambient air temperature for operation	-5...40 °C
---------------------------------------	------------

Relative humidity	0...95 %
Standards	MS IEC 60669-1 SS 227-1 BS EN 60669-1 GB 16915.1 IEC 60669-1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------