

USB-C Multiport Adapter with HDMI and VGA - 1x USB-A

Product ID: DKT30CHVCM



Ideal for mobile workers, this USB-C multiport adapter with HDMI and VGA gives you flexible video output. It's like four adapters in one, with HDMI or VGA connections, a Gigabit Ethernet port and a USB 3.0 port, all through one connection to your laptop's USB-C port. Plus, it features a hideaway cable for better cable management and easier travel.

With easy plug-and-play installation on most operating systems, the USB-C adapter doesn't require additional drivers or software. It's the perfect accessory for MacBook Pro, Dell XPS, Chromebook or other USB-C laptops.

Connect a UHD 4K HDMI or VGA Monitor

The USB Type-C multiport adapter keeps you prepared for business travel. You can extend your laptop's display by connecting to a 4K HDMI (4096x2160 or 3840 x 2160p) or VGA (1920 x 1200p) monitor or projector, to make presentations or set up a workstation.

www.startech.com
1 800 265 1844



Data Sheet

Convenient Cable Management

With multiple ports and an easily accessible hideaway cable, the USB-C all-in-one adapter makes an ideal travel dock, for easy connections on the go. Plus, the USB Type-C adapter is bus powered, so there's no need to carry around a separate power adapter.

Enhance Productivity

Connect a flash drive, mouse or other peripheral to your USB-C or Thunderbolt 3 laptop using the USB 3.0 Type-A port. The USB-C adapter adds wired network connectivity with the GbE port, making it ideal in areas without Wi-Fi.

DKT30CHVCM is backed by a StarTech.com 3-year warranty and free lifetime technical support.

www.startech.com 1 800 265 1844



Data Sheet

Certifications, Reports and Compatibility









Applications

- Make presentations in the boardroom or classroom, connecting to an HDMI or VGA monitor
- Ideal laptop accessory for mobile workers
- Convenient travel dock when working out of your hotel room
- Works well in small, shared and temporary workstations

Features

- Connect your laptop to an external HDMI or VGA monitor with this USB-C multiport adapter
- Add a USB 3.0 Type-A device, like a flash drive or mouse
- Convenient hideaway cable attached, for enhanced cable management and portability
- Add wired network connectivity with the Gigabit Ethernet RJ45 port
- Bus-powered for easy portability



Hard-to-find made easy*

Data Sheet

1 800 265 1844

	Warranty	3 Years
Hardware	4K Support	Yes
	Bus Type	USB-C
	Chipset ID	Genesys Logic - GL3523 Realtek - RTL8153 Eton Technology - EJ899T Parade Technologies - PS176 ITE -IT6516
	Displays Supported	1
	Fast-Charge Port(s)	No
	Industry Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab USB 3.0 - Backward compatible with USB 2.0 and 1.1
Performance	Auto MDIX	Yes
	Compatible Networks	10/100/1000 Mbps
	Full Duplex Support	Yes
	Maximum Analog Resolutions	1920 x 1200p @ 60Hz (VGA)
	Maximum Data Transfer Rate	5 Gbps (USB 3.0) 2 Gbps (Ethernet; Full-Duplex)
	Maximum Digital Resolutions	4096 x 2160p @ 24Hz or 3840 x 2160p @ 30Hz (HDMI)
	Type and Rate	USB 3.0 - 5 Gbit/s
	UASP Support	Yes
Connector(s)	Connector Type(s)	1 - USB Type-C (24 pin) USB 3.0 (5Gbps) Male
		1 - HDMI (19 pin) Female
		1 - VGA (15 pin, High Density D-Sub) Female
		1 - RJ-45 Female
		1 - USB Type-A (9 pin) USB 3.0 Female
Software	OS Compatibility	Windows® 7, 8, 8.1, 10 macOS 10.11 to 10.14 Chrome OS™
Special Notes / Requirements	Note	Not all USB-C ports support the full functionality of the USE Type-C standard. Ensure that your laptop USB-C port supports DP alt mode.
		Only one video output port can be used at the same time (HDMI or VGA). If two displays are connected, the HDMI port takes priority.
		A 4K-capable display is required to achieve 4K x 2K resolution (4K is also known as 4K x 2K).



Data Sheet

USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps.

System and Cable Requirements Host laptop with an available USB-C port (to ensure full functionality, the laptop's USB-C port must support DP alt mode). Power Power Source **USB-Powered** Environmental 0~90% RH Humidity 0°C to 40°C (32°F to 104°F) **Operating Temperature** -20°C to 70°C (-4°F to 158°F) Storage Temperature Physical Cable Length 3.3 in [85 mm] Characteristics Color Black Plastic Enclosure Type Product Height 0.6 in [1.6 cm] Product Length 4.1 in [10.5 cm] Product Width 2.6 in [65 mm] Weight of Product 2.9 oz [82 g] Packaging 1.8 in [45 mm] Package Height Information Package Length 6.1 in [15.5 cm] Package Width 5.2 in [13.3 cm] Shipping (Package) Weight 0.4 lb [0.2 kg] What's in the Box 1 - Multiport Adapter Included in Package 1 - Instruction Manual

Product appearance and specifications are subject to change without notice.

www.startech.com 1 800 265 1844