



Main

| | |
|---------------------------|------------------|
| Range | Lisse |
| Product or component type | Plate switch |
| Device presentation | Complete product |
| Colour tint | White |
| Quantity per set | Set of 5 |

Complementary

| | |
|-------------------------|-----------------------------------|
| Switch function | 3-pole isolator and 2-way |
| Control type | Rocker |
| Number of gangs | 1 gang |
| Pilot light | Without LED |
| Device mounting | Wall mounted |
| Rated current | 10 A, 230 V AC 10 AX, 230 V AC |
| Connections - terminals | Screw terminals |
| Material | Urea (carbamide) |
| Surface finish | Matt |
| Type of packing | Carton |
| Height | 25.5 mm |
| Width | 87 mm |
| Depth | 148 mm |
| Product weight | 0.013 kg |

Environment

| | |
|-------------------------|--------------------------------|
| Standards | BS EN 60669-1 BS EN 60947-3 |
| IP degree of protection | IP20 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.