


SMA B/H JACK STRIPPING DIM'S

檢驗重點:

- 1.裁線尺寸:309.0mm
- 2.剝線尺寸如圖所示
- 3.▲為重要量測尺寸
- 4.外觀不可損傷,電鍍不可脫落
- 5.NUT.WASHER 需鎖上



U.FL-LP-088 STRIPPING DIM'S

VSWR	INSERTION LOSS
0~3.0 GHz	
1.4: 1 Max	-1.3 dB Max

ELECTRICAL PERFORMANCE:

- 1.IMPEDANCE:50 OHMS
- 2.FREQUENCY RANGE:DC~3GHz
- 3.WORKING VOLTAGE:60Vrms MAXIMUM
- 4.DIELECTRIC WITHSTANDING VOLTAGE:200Vrms max.
- 5.INSULATOR RESISTANCE:100M OHMS min.

REACH  
RoHS

5	1	EA	U.FL-088 CONTACT	U.FL-LP-088 鍍金CONTACT For 1.37mm Cable 焊接式
4	1	EA	U.FL-LP-088HF(02)	U.FL-LP-088 Halogen Free鍍銀Shell(無鹵)白膠芯 For 1.37mm Cable
3	1	EA	R137TB-00	Ø1.37mm CABLE TIN PLATED COLOR:BLACK
2	1	EA	TUNL025BKM00	HEAT SHRINK TUBE F32 Ø2.5mm L=15.0mm COLOR:BLACK
1	1	EA	R-S132G02P-YT	SMA IP67 B/H JACK CRIMP TYPE FOR Ø1.37mm CABLE NUT x 1,WASHER x 1
ITEM	Q'TY	U/M	GTT P/N	DESCRIPTION

UNLESS OTHERWISE SPECIFIED TOLERANCE:		ANGLES: ±2°			TITLE SMA IP67 B/H JACK TO U.FL-LP-088 HF FOR OD1.37mm CABLE,L=300.0mm		C3110
XX	±0.3	DO NOT SCALE DRAWING			SIZE A4	UNIT mm	
XXX	±0.15			SCALE NA	THIRD ANGLE PROJECTION		PAGE 1 OF 3
DRAWN BY --						DATE 2016-11-08	
CHECKED BY --							
APPROVED BY --							
DWG NO. -				ITEM NO. R-132G7210300CC			
TOOLING NO. -							