

Datasheet

SAFLOK™ Self-Locking Quick Coupler

Stainless Steel

SAFLOK™ Self-Locking Quick Couplings are suitable for use with a wide variety of liquid chemicals including dyes, pharmaceutical products, adhesives, inks, cosmetics, and food products. SAFLOK™ couplings are manufactured from stainless steel, incorporate Buna-N Nitrile rubber (NBR) seals, and are designed to prevent accidental disconnection when in use (the couplings remain closed until they are manually released).

Technical Features

- May be used with any standard cam and groove coupling
- Handles automatically close and lock into the coupling body
- Conform to DIN 2828 and A-A-59326 (Mil-C-27487) specifications

Male SAFLOK Coupler – Part B (e.g. 768-2195)



Female SAFLOK Coupler – Part D (e.g. 768-2218)



Female Hose Tail SAFLOK Coupler – Part C (e.g. 768-2202)

SAFLOK Dust Cap (e.g. 768-2224)

Dimensions

RS Article Number:	Description	Type	Nominal Size (in.)	Nominal Size (mm)
768-2195	G 1 Male Saflok Coupler S/S part B	Part B	G1	25mm
768-2205	G 1 1/2 Male Saflok Coupler S/S part B	Part B	G1 1/2	40mm
768-2208	G 2 Male Saflok Coupler S/S pt.B	Part B	G2	50mm
768-2202	G 1 Hose Tail Saflok Coupler S/S part C	Part C	G1	25mm
768-2211	G 1 1/2 Hose Tail Saflok Coupler S/S,C	Part C	G1 1/2	40mm
768-2214	G 2 Hose Tail Saflok Coupler S/S part C	Part C	G2	50mm
768-2218	G 1 Female Saflok Coupler S/S part D	Part D	G1	25mm
768-2227	G 1 1/2 Female Saflok Coupler S/S pt. D	Part D	G1 1/2	40mm
768-2220	G 2 Female Saflok Coupler S/S part D	Part D	G2	50mm
768-2224	G 1 Saflok Dust Cap S/S	N/A	G1	25mm
768-2233	G 1 1/2 Saflok Dust Cap S/S	N/A	G1 1/2	40mm
768-2236	G 2 Saflok Dust Cap S/S	N/A	G2	50mm