

INDUCTION HEATERS

BETEX BLF 201 & SLF 301



10/65

min. ID Ø mm

400

max. OD Ø mm

120

max. width mm

50





max. bearing weight kg

BASIC
SERIES

BETEX BLF 201

- Portable induction heater
- Single temperature measurement
- Digital display
- 3 yokes included.

Read more about the advantages of induction heaters in the “Why use induction heating?” chapter.

Type	BETEX BLF 201 BASIC	BETEX SLF 301 SMART
Power 230V	3.0 kVA	3.0 kVA
Power 120V	1.5 kVA	1.5 kVA
Voltage/Amp standard	230V/13A	230V/13A
Voltage/Amp optional	120V/13A	120V/13A
Frequency Hz	50-60	50-60
Log functionality	No	Yes
Magnetic probe	1	2
Delta-T ΔT	No	Yes
3 yokes included, mm	Ø 7, 14, 40x50	Ø 7, 14, 40x50
Temperature check	Yes	Yes 
Time control	Yes	Yes 
Time or temperature control	No	Yes 
Temperature and speed control	No	Yes 
Max. temperature °C / °F	240 °C / 464 °F	240 °C / 464 °F
Max. time range	0-99 min.	0-99 min.
Temperature hold	Yes	Yes
Automatic demagnetization	<2A/cm	<2A/cm
Weight kg (excl. yokes)	21	21

See page 34 for detailed technical specifications.