

ENGLISH

Datasheet

RS Pro Crimp Ring Terminal, M3.5 Stud Size, 0.2mm² to 0.5mm², 26AWG to 22AWG

RS Stock No: 239-4127



Product Details

RS Pro crimp ring terminal has M3.5 stud size. It suits cables from 0.2 mm² to 0.5 mm² and 26 AWG to 22 AWG. A range of insulated crimp ring terminals made from copper with flared vinyl or nylon (mini yellow) insulation. These insulated crimp ring wire connectors are colour coded for use with different wire sizes including mini yellow 0.2 - 0.5 mm² and are available with a variety of stud sizes.



ENGLISH

Specifications:

| opcomodiono: | |
|-------------------------|---------------------|
| Colour | Yellow |
| Contact Material | Copper |
| Contact Plating | Tin |
| Inner Ring Diameter | 3.7 mm |
| Insulation Material | Nylon |
| Insulation | Insulated |
| Maximum Wire Size (AWG) | 22 AWG |
| Maximum Wire Size (mm²) | 0.5 mm ² |
| Minimum Wire Size (AWG) | 26 AWG |
| Minimum Wire Size (mm²) | 0.2 mm ² |
| Outer Ring Diameter | 6 mm |
| Overall Length | 19 mm |
| Stud Size | #6 |
| Wire Size | 26 to 22 AWG |
| Temperature Rating | +105°C |
| Amperage Rating | 5.5 to 9 A |
| Voltage Rating | 600 V |
| Туре | Single Crimp |
| | |