

**Chrome-Silver Spray****SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product Chrome-Silver Spray
Code-Nr. 111030

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

Technical Aerosols

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

| Hazard classes and Hazard categories | Hazard Statements | Classification procedure |
|--------------------------------------|-------------------|--------------------------|
|--------------------------------------|-------------------|--------------------------|

| | |
|-------------------|------------|
| Aerosol 1 | H222, H229 |
| Eye Irrit. 2 | H319 |
| STOT SE 3 | H336 |
| Aquatic Chronic 3 | H412 |

Hazard Statements

| | |
|------|---|
| H222 | Extremely flammable aerosol. |
| H229 | Pressurised container: May burst if heated. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07

Signal word

Danger

Hazard Statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

acetone, butanone, Solvent naphtha (petroleum), light arom. (NOTA P), n-butyl acetate

Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Product has an anesthetic effect.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

**Chrome-Silver Spray****! Results of PBT and vPvB assessment**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

Mixture of active ingredients with propellant

! Hazardous ingredients

| CAS No | EC No | Name | [% weight] | Classification according to Regulation (EC) No 1272/2008 [CLP/GHS] |
|------------|-----------|---|------------|--|
| 67-64-1 | 200-662-2 | acetone | 10 - 20 | Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336 |
| 78-93-3 | 201-159-0 | butanone | 3 < 10 | Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336 |
| 106-97-8 | 203-448-7 | butane | 20 < 25 | Flam. Gas 1, H220 / Press. Gas |
| 123-86-4 | 204-658-1 | n-butyl acetate | 1 < 10 | Flam. Liq. 3, H226 / STOT SE 3, H336 |
| 1330-20-7 | 215-535-7 | xylene | 5 < 10 | Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Acute Tox. 4, H312 / Skin Irrit. 2, H315 |
| 64742-95-6 | 265-199-0 | Solvent naphtha (petroleum), light arom. (NOTA P) | 2,5 < 10 | Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H335, H336 / Aquatic Chronic 2, H411 / Skin Irrit.2, H315 / , EUH066 |
| 7429-90-5 | 231-072-3 | aluminium powder (stabilised) | 1 < 10 | Flam. Sol. 1, H228 / |
| 74-98-6 | 200-827-9 | propane | 20 < 25 | Flam. Gas 1, H220 / Press. Gas, H280 |

REACH

| CAS No | Name | REACH registration number |
|------------|---|---------------------------|
| 67-64-1 | acetone | 01-2119471330-49 |
| 78-93-3 | butanone | 01-2119457290-43 |
| 106-97-8 | butane | 01-2119474691-32 |
| 123-86-4 | n-butyl acetate | 01-2119485493-29 |
| 1330-20-7 | xylene | 01-2119488216-32 |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. (NOTA P) | 01-2119455851-35 |
| 7429-90-5 | aluminium powder (stabilised) | 01-2119529243-45 |
| 74-98-6 | propane | 01-2119486944-21 |

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.



Chrome-Silver Spray

In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

Unconsciousness

vomiting

Respiratory complaints

Anaesthetic state

Headache

Confusion

Dizziness

skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

! SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

sand

Unsuitable extinguishing media

water

Full water jet

5.2. Special hazards arising from the substance or mixture

Danger of bursting

In case of fire formation of dangerous gases possible.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

! Additional information

Vapours are heavier than air and will spread on the ground.

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material.

After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

! SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink, smoke or take drugs.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

Avoid effect of heat.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

! Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

! Further information on storage conditions

Store at +5 till +25 °C.

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Store in a dry place.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

**Chrome-Silver Spray****! SECTION 8: Exposure controls/personal protection****8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

| CAS No | Name | Code | [mg/m3] | [ppm] | Remark |
|-----------|-------------------------------------|------------|---------|-------|-----------|
| 67-64-1 | Acetone | 8 hours | 1210 | 500 | EH40/2005 |
| | | Short-term | 3620 | 1500 | |
| 106-97-8 | Butane | 8 hours | 1450 | 600 | EH40/2005 |
| | | Short-term | 1810 | 750 | |
| 78-93-3 | Butan -2-one (methyl ethyl ketone) | 8 hours | 600 | 200 | EH40/2005 |
| | | Short-term | 899 | 300 | |
| 1330-20-7 | Xylene, o-, m-, p- or mixed isomers | 8 hours | 220 | 50 | EH40/2005 |
| | | Short-term | 441 | 100 | |

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

| CAS No | Name | Code | [mg/m3] | [ppm] | Remark |
|-----------|-----------------------------|------------|---------|-------|--------|
| 1330-20-7 | xylene, mixed isomers, pure | 8 hours | 221 | 50 | skin |
| | | Short-term | 442 | 100 | |
| 67-64-1 | acetone | 8 hours | 1210 | 500 | |
| 78-93-3 | butanone | 8 hours | 600 | 200 | |
| | | Short-term | 900 | 300 | |

DNEL-/PNEC-values**DNEL worker**

| CAS No | Substance name | Value | Code | Remark |
|------------|---|------------|--|--------|
| 123-86-4 | n-butyl acetate | 11 mg/kg | DNEL long-term dermal (systemic) | |
| | | 960 mg/m3 | DNEL acute inhalative (systemic) | |
| | | 300 mg/m3 | DNEL long-term inhalative (local) | |
| | | 600 mg/m3 | DNEL acute inhalative (local) | |
| | | 480 mg/m3 | DNEL long-term inhalative (systemic) | |
| | | 11 mg/kg | DNEL acute dermal, short-term (systemic) | |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. (NOTA P) | 2 mg/kg | DNEL short-term oral (acute) | |
| | | 25 mg/kg | DNEL long-term dermal (systemic) | |
| | | 150 mg/m3 | DNEL long-term inhalative (systemic) | |
| 67-64-1 | acetone | 186 mg/kg | DNEL long-term dermal (systemic) | |
| | | 1210 mg/m3 | DNEL long-term inhalative (systemic) | |
| | | 2420 mg/m3 | DNEL acute inhalative (local) | |
| 7429-90-5 | aluminium powder (stabilised) | 3,72 mg/m3 | DNEL long-term inhalative (local) | |
| 78-93-3 | butanone | 1161 mg/kg | DNEL long-term dermal (systemic) | |
| | | 600 mg/m3 | DNEL long-term inhalative (systemic) | |



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

05.08.2019

revision

26.09.2017 (GB) Version 8.8

Chrome-Silver Spray

PNEC

| CAS No | Substance name | Value | Code | Remark |
|------------|---|-------------|-----------------------------------|--------|
| 123-86-4 | n-butyl acetate | 0,18 mg/l | PNEC aquatic, freshwater | |
| | | 0,981 mg/kg | PNEC sediment, freshwater | |
| | | 0,018 mg/l | PNEC aquatic, marine water | |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. (NOTA P) | 0,99 mg/kg | PNEC soil, marine water | |
| 67-64-1 | acetone | 1,06 mg/l | PNEC aquatic, marine water | |
| | | 30,4 mg/kg | PNEC sediment, freshwater | |
| | | 10,6 mg/l | PNEC aquatic, freshwater | |
| | | 3,04 mg/kg | PNEC sediment, marine water | |
| 7429-90-5 | aluminium powder (stabilised) | 20 mg/l | PNEC sewage treatment plant (STP) | |
| | | 0,0749 mg/l | PNEC aquatic, freshwater | |

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

! Hand protection

Gloves (solvent-resistant)

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

! SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

aerosol

Colour

silver-grey

Odour

characteristic

Odour threshold

not determined

Important health, safety and environmental information

| | Value | Temperature | at | Method | Remark |
|----------|----------------|-------------|----|--------|--------|
| pH value | not determined | | | | |



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 26.09.2017 (GB) Version 8.8

Chrome-Silver Spray

| | Value | Temperature | at | Method | Remark |
|--|----------------|-------------|----|--------|-----------------------------------|
| boiling point | -44 °C | | | | |
| Melting point / Freezing point | not determined | | | | |
| Flash point | not applicable | | | | Aerosol |
| Vapourisation rate | not determined | | | | |
| Flammable (solid) | not determined | | | | |
| Flammability (gas) | not determined | | | | |
| Ignition temperature | > 200 °C | | | | estimate |
| Self ignition temperature | | | | | The product is not self-igniting. |
| Lower explosion limit | 1,5 Vol-% | | | | |
| Upper explosion limit | 13 Vol-% | | | | |
| Vapour pressure | not determined | 20 °C | | | |
| Relative density | not determined | | | | |
| Vapour density | not determined | | | | |
| Solubility in water | | | | | insoluble |
| Solubility/other | not determined | | | | |
| Partition coefficient n-octanol/water (log P O/W) | not determined | | | | |
| Decomposition temperature | not determined | | | | |
| Viscosity dynamic | not determined | | | | |
| Viscosity kinematic | not determined | | | | |

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information

No information available.

**! SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.

Formation of explosive gas/air mixtures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products**Thermal decomposition**

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

| | Value/Validation | Species | Method | Remark |
|------------------------------|-------------------|---------|----------|-----------------|
| LD50 acute oral | 2000 - 5000 mg/kg | rat | | CAS: 64742-95-6 |
| LD50 acute dermal | 1100 mg/kg | | estimate | ATE |
| LC50 acute inhalation | > 5 mg/l (4 h) | rat | estimate | ATE |
| Skin irritation | irritant | | | |
| Eye irritation | irritant | | | |

Subacute Toxicity - Carcinogenicity

| | Value | Species | Method | Validation |
|------------------------------|-------|---------|--------|---|
| Mutagenicity | | | | No experimental information on genotoxicity in vitro available. |
| Reproduction-Toxicity | | | | No indications of toxic effects were observed in reproduction studies in animals. |
| Carcinogenicity | | | | No indications of carcinogenic effects are available from long-term trials. |

! Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.



Chrome-Silver Spray

Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

Vapours may cause dizziness, headaches and tiredness

May cause vomiting.

Product may cause irreversible eye injuries.

Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

! SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

! General regulation

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

! SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

16 05 04*

Name of waste

gases in pressure containers (including halons) containing hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

! General information

For proper waste disposal a complete emptying of the tin is necessary.

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**Chrome-Silver Spray****! SECTION 14: Transport information**

| | ADR/RID | IMDG | IATA-DGR |
|---|----------------|-------------|---------------------|
| 14.1. UN number | 1950 | 1950 | 1950 |
| 14.2. UN proper shipping name | AEROSOLS | AEROSOLS | Aerosols, flammable |
| 14.3. Transport hazard class(es) | 2.1 | 2.1 | 2.1 |
| 14.4. Packing group | - | - | - |
| 14.5. Environmental hazards | No | No | No |

14.6. Special precautions for user

Caution: Gases

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
not applicable**Land and inland navigation transport ADR/RID**

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

Transport as limited quantities according to 3.4 IMDG Code is possible.

! Transport/further information

Marine pollutant: NO

! SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard****VOC content** 89 %**VOC value** 627,2 g/L**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.7



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 26.09.2017 (GB) Version 8.8

Chrome-Silver Spray

- EUH066 Repeated exposure may cause skin dryness or cracking.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335, -?-
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.