



**! SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Name of product** Anti Friction Spray MoS2  
Code-Nr. 115390

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Recommended intended purpose(s)**

Technical Aerosols

**1.3. Details of the supplier of the safety data sheet**

**Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster  
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone : +49(0)251 / 9322 - 0  
Fax : +49(0)251 / 9322 - 244  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:  
++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South  
Africa (24h): Tel: ++44 1865 407333 (English)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number**

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):  
Tel: ++49 69 222 25285 (Deutsch, Englisch)

**! SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories      Hazard Statements      Classification procedure

|                          |                   |
|--------------------------|-------------------|
| <b>Aerosol 1</b>         | <b>H222, H229</b> |
| <b>Skin Irrit. 2</b>     | <b>H315</b>       |
| <b>Eye Dam. 1</b>        | <b>H318</b>       |
| <b>Aquatic Chronic 3</b> | <b>H412</b>       |

**Hazard Statements**

|      |   |
|------|---|
| H222 | Extremely flammable aerosol.                |
| H229 | Pressurised container: May burst if heated. |
| H315 | Causes skin irritation.                     |
| H318 | Causes serious eye damage.                  |

H412 Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS05

### ! Signal word

Danger

### Hazard Statements

H222 Extremely flammable aerosol.  
 H229 Pressurised container: May burst if heated.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H412 Harmful to aquatic life with long lasting effects.

### Precautionary Statements

P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe vapours/spray.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/eye protection.  
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
 P332 + P313 If skin irritation occurs: Get medical advice/attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.  
 P403 + P235 Store in a well-ventilated place. Keep cool.  
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 P501 Dispose of contents/container to hazardous or special waste collection point.

### ! Hazardous ingredients for labeling

n-Butylpolytitanat, Naphtha (petroleum), hydrotreated light

### Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

### ! Special rules for supplemental label elements for certain mixtures

Contains Hydrocarbons-Terpene .May produce an allergic reaction.

## 2.3. Other hazards

Product has an anesthetic effect.

**Information pertaining to special dangers for human and environment**

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**! SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

**3.2. Mixtures****Description**

Mixture of active ingredients with propellant

**! Hazardous ingredients**

| CAS No     | EC No     | Name                                    | [% weight]   | Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]  |
|------------|-----------|---|--------------|---|
| 75-28-5    | 200-857-2 | isobutane                               | 2,5 - 10     | Flam. Gas 1, H220 / Press. Gas  |
| 106-97-8   | 203-448-7 | butane                                  | 50 - 70      | Flam. Gas 1, H220 / Press. Gas  |
| 110-54-3   | 203-777-6 | n-hexane                                | 0,25 < 1     | Flam. Liq. 2, H225 / Repr. 2, H361f / Asp. Tox. 1, H304 / STOT RE 2, H373 / Skin Irrit. 2, H315 / STOT SE 3, H336 / Aquatic Chronic 2, H411 |
| 110-82-7   | 203-806-2 | cyclohexane                             | 0,025 < 0,25 | Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Skin Irrit. 2, H315 / STOT SE 3, H336 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410            |
| 74-98-6    | 200-827-9 | propane                                 | 10 - 25      | Flam. Gas 1, H220 / Press. Gas, H280  |
| 68956-56-9 | 273-309-3 | Hydrocarbons-Terpene                    | 0,25 < 1     | Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411                                 |
| 64742-49-0 | 921-024-6 | Naphtha (petroleum), hydrotreated light | 10 < 15      | Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / Skin Irrit. 2, H315 / STOT SE 3, H336                                    |
| 9022-96-2  | 638-841-6 | n-Butylpolytitanat                      | 3 < 10       | Eye Dam. 1, H318  |

**REACH**

| CAS No     | Name                                    | REACH registration number |
|------------|---|---------------------------|
| 75-28-5    | isobutane                               | 01-2119485395-27          |
| 106-97-8   | butane                                  | 01-2119474691-32          |
| 110-54-3   | n-hexane                                | 01-2119480412-44          |
| 110-82-7   | cyclohexane                             | 01-2119463273-41          |
| 74-98-6    | propane                                 | 01-2119486944-21          |
| 68956-56-9 | Hydrocarbons-Terpene                    | 01-2119980606-28          |
| 64742-49-0 | Naphtha (petroleum), hydrotreated light | 01-2119475514-35          |
| 9022-96-2  | n-Butylpolytitanat                      | polymer                   |

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

**In case of inhalation**

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

**In case of skin contact**

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.



---

**In case of eye contact**

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

**In case of ingestion**

Seek medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

---

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Dry powder  
Carbon dioxide  
sand

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Danger of bursting  
In case of fire formation of dangerous gases possible.

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

**Additional information**

Cool endangered containers with water spray jet.  
Collect contaminated firefighting water separately, must not be discharged into the drains.

---

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Ensure adequate ventilation.  
Use personal protective clothing.  
Keep away sources of ignition.

**6.2. Environmental precautions**

Inform pollution control authorities if product gets into the sewerage systems or open waters.  
Do not discharge into the drains or bodies of water.  
Do not discharge into the drains/surface waters/groundwater.

**6.3. Methods and material for containment and cleaning up**

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).  
After taking up the material dispose according to regulation.

**Additional Information**

Sort out leaky cans and dispose according to regulations.

**6.4. Reference to other sections**

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

**! SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**General protective measures**

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

**Hygiene measures**

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

Avoid effect of heat.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

**! Further information on storage conditions**

Store only at temperature of 30°C maximum (=86°F).

Protect from heat and direct solar radiation.

Store container at cool and aired place.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**! SECTION 8: Exposure controls/personal protection****8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

| CAS No   | Name        | Code         | [mg/m3] | [ppm] | Remark    |
|----------|-------------|--------------|---------|-------|-----------|
| 106-97-8 | Butane      | 8 hours      | 1450    | 600   | EH40/2005 |
|          |             | Short-term   | 1810    | 750   |           |
| 110-82-7 | Cyclohexane | 8 hours      | 350     | 1050  | EH40/2005 |
|          |             | Short-term   | 1050    | 300   |           |
| 110-54-3 | n-hexane    | 8 hours      | 72      | 20    | EH40/2005 |
| 106-97-8 | Butan (CH)  | MAK, 8 hours | 1900    | 800   | ZNS       |
|          |             | Short-term   | 7600    | 3200  |           |



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 09.04.2019 (GB) Version 9.0

**Anti Friction Spray MoS2****Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)**

| CAS No   | Name        | Code    | [mg/m3] | [ppm] | Remark |
|----------|-------------|---------|---------|-------|--------|
| 110-54-3 | n-hexane    | 8 hours | 72      | 20    |        |
| 110-82-7 | cyclohexane | 8 hours | 700     | 200   |        |

**DNEL-/PNEC-values****DNEL worker**

| CAS No     | Substance name                          | Value      | Code                                 | Remark |
|------------|---|------------|--------------------------------------|--------|
| 110-54-3   | n-hexane                                | 75 mg/m3   | DNEL long-term inhalative (systemic) |        |
| 110-82-7   | cyclohexane                             | 700 mg/m3  | DNEL long-term inhalative (systemic) |        |
|            |   | 700 mg/m3  | DNEL acute inhalative (systemic)     |        |
| 64742-49-0 | Naphtha (petroleum), hydrotreated light | 773 mg/kg  | DNEL long-term dermal (systemic)     |        |
|            |   | 2038 mg/m3 | DNEL long-term inhalative (systemic) |        |

**PNEC**

| CAS No   | Substance name | Value          | Code                               | Remark |
|----------|----------------|----------------|------------------------------------|--------|
| 110-82-7 | cyclohexane    | 3,627 mg/kg dw | PNEC sediment, marine water        |        |
|          |                | 3,24 mg/l      | PNEC sewage treatment plant (STP)  |        |
|          |                | 0,207 mg/l     | PNEC aquatic, intermittent release |        |

**! Additional advice**

The statutory local and national regulations have to be observed.

**8.2. Exposure controls****Respiratory protection**

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

**Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

**Eye protection**

tightly fitting goggles

**Other protection measures**

protective clothing

**Appropriate engineering controls**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.



**Oxidising properties**

No information available.

**Explosive properties**

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

**9.2. Other information**

No information available.

**! SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

The product is chemically stable under recommended conditions of storage, use and temperature.

**10.3. Possibility of hazardous reactions**

No hazardous reactions known.

**10.4. Conditions to avoid**

Keep away from heat.

Formation of explosive gas/air mixtures.

Risk of bursting.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

Gases/vapours, flammable

Carbon dioxide (CO<sub>2</sub>)

Carbon monoxide

**Thermal decomposition**

Remark No decomposition if used as directed.

**! SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

|                              | Value/Validation            | Species | Method | Remark          |
|------------------------------|-----------------------------|---------|--------|-----------------|
| <b>LD50 acute oral</b>       | > 2000 mg/kg                | rat     |        | CAS: 64742-49-0 |
| <b>LD50 acute dermal</b>     | > 2000 mg/kg                | rabbit  |        | CAS: 64742-49-0 |
| <b>LC50 acute inhalation</b> | > 20 mg/l (4 h)             | rat     |        | Isobutane       |
| <b>Skin irritation</b>       | irritant                    |         |        |                 |
| <b>Eye irritation</b>        | risk of strong eye injuries |         |        |                 |
| <b>Skin sensitization</b>    | non-sensitizing             |         |        |                 |



**Subacute Toxicity - Carcinogenicity**

| Value                        | Species | Method | Validation  |
|------------------------------|---------|--------|---|
| <b>Mutagenicity</b>          |         |        | No experimental information on genotoxicity in vitro available.                   |
| <b>Reproduction-Toxicity</b> |         |        | No indications of toxic effects were observed in reproduction studies in animals. |
| <b>Carcinogenicity</b>       |         |        | No indications of carcinogenic effects are available from long-term trials.       |

**! Experiences made from practice**

May irritate the mucosae.

Risk of strong eye injuries.

Frequent persistent contact with the skin may cause skin irritation.

**Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

**! SECTION 12: Ecological information****12.1. Toxicity****Ecotoxicological effects**

| Value                             | Species | Method | Validation      |
|-----------------------------------|---------|--------|-----------------|
| <b>Fish</b> LC50 < 10 mg/l (96 h) | Fish    |        | CAS: 64742-49-0 |

**12.2. Persistence and degradability**

No information available.

**12.3. Bioaccumulative potential**

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects****! General regulation**

Harmful to aquatic life with long lasting effects.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.



## ! SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

| ! Waste code No. | Name of waste   |
|------------------|---|
| 15 01 04         | metallic packaging  |
| 16 05 04*        | gases in pressure containers (including halons) containing hazardous substances |

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

### Recommendations for the product

Remove in accordance with local official regulations.

### ! Recommendations for packaging

Dispose of according to the local waste regulations.  
Totally emptied packaging may be taken for recycling.

### General information

For proper waste disposal a complete emptying of the tin is necessary.

## SECTION 14: Transport information

|                                  | ADR/RID  | IMDG     | IATA-DGR            |
|----------------------------------|----------|----------|---------------------|
| 14.1. UN number                  | 1950     | 1950     | 1950                |
| 14.2. UN proper shipping name    | AEROSOLS | AEROSOLS | Aerosols, flammable |
| 14.3. Transport hazard class(es) | 2.1      | 2.1      | 2.1                 |
| 14.4. Packing group              | -        | -        | -                   |
| 14.5. Environmental hazards      | No       | No       | No                  |

### 14.6. Special precautions for user

Caution: Gases

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code  
not applicable

### Land and inland navigation transport ADR/RID

Hazard label(s) 2.1  
tunnel restriction code D  
Classification code 5F  
transport in "limited quantities" according to 3.4 ADR is possible

### Transport/further information

Marine pollutant: NO

## ! SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| ! VOC standard |            |
|----------------|------------|
| VOC content    | 90 %       |
| VOC value      | ca.615 g/L |



---

## 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

---

## ! SECTION 16: Other information

### ! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

### Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.8

|       |  |
|-------|--|
| H220  | Extremely flammable gas.   |
| H225  | Highly flammable liquid and vapour.  |
| H226  | Flammable liquid and vapour.   |
| H280  | Contains gas under pressure; may explode if heated.  |
| H304  | May be fatal if swallowed and enters airways.  |
| H315  | Causes skin irritation.  |
| H317  | May cause an allergic skin reaction.   |
| H318  | Causes serious eye damage.   |
| H336  | May cause drowsiness or dizziness.   |
| H361f | Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).                       |
| H373  | May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). |
| H400  | Very toxic to aquatic life.  |
| H410  | Very toxic to aquatic life with long lasting effects.  |
| H411  | Toxic to aquatic life with long lasting effects.   |