


NO	DESCRIPTION	DATE
①	BACKGROUND FORMAT UPDATED	01.22.03'
②	34.8±0.5 → 33.5±0.5	08.05.05'
③	BACKGROUND FORMAT UPDATED	01.08.09'
④	DEL. PROOF VOLTAGE WORKING VOLTAGE → VOLTAGE RATING	11.27.12'
⑤	ADD VSWR	03.19.14'



1.0 ELECTRICAL

- 1.1 FREQUENCY RANGE: DC-300 MHz
 1.2 NOMINAL IMPEDANCE: 50 OHMS
 1.3 VOLTAGE RATING: 500 VOLTS MAX. ④
 1.4 VSWR: 1.3 MAX. ⑤

2.0 MATERIALS

- 2.1 BODIES: BRASS PER JIS-C3604
 2.2 CENTER CONTACT: BRASS PER JIS-C3604

3.0 FINISHES AND OTHERS

- 3.1 SEE BELOW TABLE FOR DETAILS.

4.0 ENVIRONMENTAL

- 4.1 OPERATING TEMPERATURE RANGE: -40° C TO +60° C

NO	DESCRIPTION	MATERIAL	Q'TY	FINISH
6	INSULATION	POM	1	NONE
5	BODY	BRASS	1	NICKEL 100μ" MIN.
4	CENTER CONTACT	BRASS	1	GOLD
3	WASHER	BRASS	1	NONE
2	INSULATION	POM	1	NONE
1	SHELL	BRASS	1	NICKEL 100μ" MIN.

APPROVED

by _____ DATE: _____



DESCRIPTION		STRAIGHT UHF PLUG-N JACK ADAPTER						
製圖	DRAWN	TOLERANCE	品名	17-18 D.G.N	日期	DATE	版次	REV.
	Yoko							
檢圖	CHECK	APPROVAL	XXX ±0.05	UNIT	DWG.NO.	17-0077	SCALE	比例
	Arc							
認定	Angela	ANGLE	±5°					