


Product data sheet

Characteristics

GGBL3050S

Lisse - unswitched socket - 13 A - 1 gang - 230 V - white



Main

Range	Lisse
Aesthetic name	White moulded
Product or component type	Unswitched socket
Device presentation	Complete product
Outlet standard	British
Colour tint	Matt white
Quantity per set	Set of 1
Type of packing	Bag

Complementary

Switch function	1-pole
Rated current	13 A, 230 V AC 50 Hz :
Actuator	Rocker
Number of gangs	1 gang
Fixing mode	By screws
Connections - terminals	Screw terminals
Material	Urea (carbamide)
Type of installation	Indoor
Depth	87 mm
Width	87 mm
Height	27 mm
Product weight	0.08 kg

Environment

Standards	BS 1363-2
IP degree of protection	IP20

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.