

## **FEATURES**

- Quick connection and disconnection
- Large range to comply food norms
- Silicon free
- Operating temperature range is from - 15 °C to + 190 °C

# RS PRO STRAIGHT MALE ADAPTOR (PARALLEL) -FOOD GRADE

RS Stock No.: 2312745



RS PROfessionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

# Pneumatic Quick Connect Couplings



### **Product Description**

The RS PRO straight male adaptor (parallel) works in - 0.99 bar to 20 bar pressure range. It is mainly used in dairy, coffee machine, vending, food & beverage, medical, vacuum applications. It is available in brass with Food Grade coating. In combination with FEP tubes, it is the most demanded solution for the Food & Beverage market. Beacause of the special coating it can be used also in agressive environment.

RoHS and REACH compliant.

#### **General Specifications**

Material	Nickel Plated Brass		
Applications	Lubrication System, Cooling System, Pneumatic		
pplications	Machinery Equipment		

#### **Mechanical Specifications**

Connection Type	Threaded, Tube		
Hose Barb Connection	6mm		
Coupling Gender	Male		
Threaded Connection	1/8 in Male		
Thread Size	1/8in		
Hose Barb Connection	6mm		
Mounting Hole Diameter	13mm		
Wrench Size1	13		
Wrench Size2	4		
Length	23.5mm		




# **Operation Environment Specifications**

Minimum Operating Temperature	-15°C
Maximum Operating Temperature	190°C

## **Similar Products**

Parameters	2312521	2312522	
Brand	RS PRO	RS PRO	
Connection Type	Threaded, Tube	Threaded, Tube	
Tube Connection Size	9mm	10mm	
Coupling Gender	Male	Male	
Threaded Connection	3/8 in Male	1/2 in Male	
Thread Size	3/8in	1/2in	
Hose Barb Connection	30.5mm	25Hex	
Wrench Size	20Hex	54mm	





Tube	Α	В	С	L	CH1	CH2	Pack.
6	1/8	5.4	13	23.5	13	4	10