



Benefits

- No external driver required which facilitates easy installation and maintenance
- Delivers uniform light distribution
- IP44 rated diffuser versions for damp locations such as bathrooms and kitchens
- Anti-glare, UGR 19 for eye comfort

Application



Home



Shopping Mall



Retail



Office

Model	Item Description	W	PF	lm	lm/W	CRI	BA	W	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (PCS/CTN)
F54200RC-WH	SIENA SR 6" R150 15.5W 2800K 90D WH	15.5	>0.9	1560	101	80	90°	50000	180*180*120	390*560*500	24

Technical Specifications	
CRI	80
Colour Consistency (SDCM)	≤ 6
Dimmable	No
Housing Colour	White
IP	IP44
IK	IK02
Driver integrated (Yes/No)	Yes



Electrical Supply	
Frequency (Hz)	50/60Hz
Voltage (V)	220V-240V
AC/DC	AC

Mechanical Properties	
Optical Material	Reflector
Housing Material	PC


Application Conditions	
Operating Temperature	-20°C~40°C
Application Temperature	20°C
Storage Environment	-20°C~40°C

Photometric Data

F54200RC



Dimensional Drawing



F54200RC