

# ATV71LD17N4Z

variable speed drive Altivar Lift, 7.5 kW 10Hp,  
380...480 V three-phase, EMC filter, with heat  
sink



## Main

Device short name	ATV71
Product destination	Asynchronous motors Synchronous motors
Network number of phases	3 phases
Supply voltage limits	323...528 V
Supply frequency	50...60 Hz - 5...5 %
Motor power kW	7.5 kW, 3 phases at 380...480 V
Motor power hp	10 hp, 3 phases at 380...480 V
Line current	27 A for 380 V 3 phases 7.5 kW / 10 hp 22.2 A for 480 V 3 phases 7.5 kW / 10 hp
Range of product	Altivar Lift
Product or component type	Variable speed drive
Product specific application	Lift
Variant	With integrated 7-segment display terminal
Communication port protocol	CANopen Modbus
[Us] rated supply voltage	380...480 V - 15...10 %
EMC filter	Integrated

## Complementary

Apparent power	17.8 kVA at 380 V 3 phases 7.5 kW / 10 hp
Prospective line I <sub>sc</sub>	22 kA for 3 phases
Nominal output current	17.6 A at 4 kHz 380 V 3 phases 7.5 kW / 10 hp 14 A at 4 kHz 460 V 3 phases 7.5 kW / 10 hp
Maximum transient current	23.9 A for 2 s 3 phases / 7.5 kW / 10 hp
Speed drive output frequency	0...599 Hz
Speed range	1...100 for asynchronous motor in open-loop mode, without speed feedback 1...50 for synchronous motor in open-loop mode, without speed feedback 1...1000 for asynchronous motor in closed-loop mode with encoder feedback
Torque accuracy	+/- 5 % in closed-loop mode with encoder feedback +/- 15 % in open-loop mode, without speed feedback
Transient overtorque	170 %, +/- 10 % for 60 s 220 %, +/- 10 % for 2 s
Braking torque	30 % without braking resistor ≤ 150 % with braking or hoist resistor
Local signalling	1 LED (red) for drive voltage
Output voltage	≤ power supply voltage
Insulation	Electrical between power and control
Type of cable for external connection	Without mounting kit: 1 wire(s)IEC cable at 45 °C, copper 90 °C / XLPE/EPR Without mounting kit: 1 wire(s)IEC cable at 45 °C, copper 70 °C / PVC With an IP21 or an IP31 kit: 3 wire(s)IEC cable at 40 °C, copper 70 °C / PVC With a NEMA Type1 kit: 3 wire(s)UL 508 cable at 40 °C, copper 75 °C / PVC
Electrical connection	Terminal, clamping capacity: 2.5 mm <sup>2</sup> , AWG 14 (AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR) Terminal, clamping capacity: 6 mm <sup>2</sup> , AWG 8 (L1/R, L2/S, L3/T, U/T1, V/T2, W/T3, PC/-, PO, PA/+, PA, PB)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Tightening torque	3 N.M, 26.5 lb.in (L1/R, L2/S, L3/T, U/T1, V/T2, W/T3, PC/-, PO, PA/+, PA, PB) 0.6 N.m (AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)
Supply	Internal supply for reference potentiometer (1 to 10 kOhm): 10.5 V DC +/- 5 %, <10 A, protection type: overload and short-circuit protection Internal supply: 24 V DC (21...27 V), <200 A, protection type: overload and short-circuit protection
Sampling duration	2 Ms +/- 0.5 ms (LI6)if configured as logic input - discrete input(s) 2 Ms +/- 0.5 ms (LI1...LI5) - discrete input(s) 2 Ms +/- 0.5 ms (AI1-/AI1+) - analog input(s) 2 ms +/- 0.5 ms (AI2) - analog input(s)
Response time	R1A, R1B, R1C 7 ms, tolerance +/- 0.5 ms for discrete output(s) R2A, R2B 7 ms, tolerance +/- 0.5 ms for discrete output(s) AO1 2 ms, tolerance +/- 0.5 ms for analog output(s) <= 100 ms in STO (Safe Torque Off)
Accuracy	+/- 0.6 % (AI1-/AI1+) for a temperature variation 60 °C +/- 0.6 % (AI2) for a temperature variation 60 °C +/- 1 % (AO1) for a temperature variation 60 °C
Linearity error	+/- 0.15 % of maximum value (AI1-/AI1+, AI2) +/- 0.2 % (AO1)
Analogue output type	AO1 software-configurable voltage: 0...10 V DC, impedance: 470 Ohm, resolution 10 bits AO1 software-configurable current: 0...20 mA, impedance: 500 Ohm, resolution 10 bits AO1 software-configurable logic output 10 V 20 A
Discrete output type	Configurable relay logic: (R1A, R1B, R1C) NO/NC - 100000 cycles Configurable relay logic: (R2A, R2B) NO - 100000 cycles
Minimum switching current	3 mA at 24 V DC for configurable relay logic
Maximum switching current	5 A at 250 V AC on resistive load - cos phi = 1 - L/R = 0 ms (R1, R2) 5 A at 30 V DC on resistive load - cos phi = 1 - L/R = 0 ms (R1, R2) 2 A at 250 V AC on inductive load - cos phi = 0.4 - L/R = 7 ms (R1, R2) 2 A at 30 V DC on inductive load - cos phi = 0.4 - L/R = 7 ms (R1, R2)
Discrete input type	Programmable (LI1...LI5)24 V DC, with level 1 PLC - 3500 Ohm Switch-configurable (LI6)24 V DC, with level 1 PLC - 3500 Ohm Switch-configurable PTC probe (LI6) - 0...6 probes - 1500 Ohm Safety input (PWR)24 V DC - 1500 Ohm
Discrete input logic	Positive logic (LI6)if configured as logic input, < 5 V (state 0), > 11 V (state 1) Negative logic (LI6)if configured as logic input, > 16 V (state 0), < 10 V (state 1) Positive logic (LI1...LI5), < 5 V (state 0), > 11 V (state 1) Negative logic (LI1...LI5), > 16 V (state 0), < 10 V (state 1) Positive logic (PWR), < 2 V (state 0), > 17 V (state 1)
Dielectric strength	3535 V DC between earth and power terminals 5092 V DC between control and power terminals
Insulation resistance	> 1 mOhm 500 V DC for 1 minute to earth
Frequency resolution	Display unit: 0.1 Hz Analog input: 0.024/50 Hz
Connector type	1 RJ45 (on front face) for Modbus 1 RJ45 (on terminal) for Modbus Male SUB-D 9 on RJ45 for CANopen
Physical interface	2-wire RS 485 for Modbus
Transmission frame	RTU for Modbus
Transmission rate	9600 bps, 19200 bps for Modbus on front face 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps for Modbus on terminal 20 kbps, 50 kbps, 125 kbps, 250 kbps, 500 kbps, 1 Mbps for CANopen
Data format	8 bits, 1 stop, even parity for Modbus on front face 8 bits, odd even or no configurable parity for Modbus on terminal
Type of polarization	No impedance for Modbus
Number of addresses	1...247 for Modbus 1...127 for CANopen

Control options	<ul style="list-style-type: none"> <li>Communication card for Modbus TCP</li> <li>Communication card for Fipio</li> <li>Communication card for Modbus/Uni-Telway</li> <li>Communication card for Modbus Plus</li> <li>Communication card for EtherNet/IP</li> <li>Communication card for DeviceNet</li> <li>Communication card for Profibus DP</li> <li>Communication card for Profibus DP V1</li> <li>Communication card for Interbus-S</li> <li>Communication card for CC-Link</li> <li>Interface card for encoder</li> <li>I/O extension card</li> <li>Controller inside programmable card</li> <li>Overhead crane card</li> </ul>
Discrete input number	7
Discrete output number	2
Analogue input number	2
Analogue input type	<ul style="list-style-type: none"> <li>AI2 software-configurable voltage: 0...10 V DC 24 V max, impedance: 30000 Ohm, resolution 11 bits</li> <li>AI1-/AI1+ bipolar differential voltage: +/- 10 V DC 24 V max, resolution 11 bits + sign</li> <li>AI2 software-configurable current: 0...20 mA, impedance: 242 Ohm, resolution 11 bits</li> </ul>
Analogue output number	1
Method of access	Slave CANopen
Asynchronous motor control profile	<ul style="list-style-type: none"> <li>Flux vector control without sensor, ENA (energy Adaptation) system</li> <li>Flux vector control with sensor, standard</li> <li>Voltage/Frequency ratio - Energy Saving, quadratic U/f</li> <li>Flux vector control without sensor, standard</li> <li>Voltage/Frequency ratio, 5 points</li> <li>Flux vector control without sensor, 2 points</li> <li>Voltage/frequency ratio, 2 points</li> </ul>
Synchronous motor control profile	<ul style="list-style-type: none"> <li>Vector control with sensor, standard</li> <li>Vector control without sensor, standard</li> </ul>
Acceleration and deceleration ramps	<ul style="list-style-type: none"> <li>Automatic adaptation of ramp if braking capacity exceeded, by using resistor</li> <li>Linear adjustable separately from 0.01 to 9000 s</li> <li>S, U or customized</li> </ul>
Motor slip compensation	<ul style="list-style-type: none"> <li>Not available in voltage/frequency ratio (2 or 5 points)</li> <li>Automatic whatever the load</li> <li>Adjustable</li> <li>Suppressable</li> </ul>
Switching frequency	1...16 kHz adjustable
Nominal switching frequency	8 kHz
Minimum braking resistance	12 Ohm
Network frequency	47.5...63 Hz
Protection type	<ul style="list-style-type: none"> <li>Overheating protection: drive</li> <li>Thermal protection: drive</li> <li>Short-circuit between motor phases: drive</li> <li>Input phase breaks: drive</li> <li>Overcurrent between output phases and earth: drive</li> <li>Overvoltages on the DC bus: drive</li> <li>Break on the control circuit: drive</li> <li>Against exceeding limit speed: drive</li> <li>Line supply undervoltage: drive</li> <li>Line supply overvoltage: drive</li> <li>Against input phase loss: drive</li> <li>Thermal protection: motor</li> <li>Motor phase break: motor</li> <li>Power removal: motor</li> </ul>

## Environment

Pollution degree	2 conforming to EN/IEC 61800-5-1
IP degree of protection	IP20 on upper part without blanking plate on cover conforming to EN/IEC 61800-5-1 IP20 on upper part without blanking plate on cover conforming to EN/IEC 60529 IP21 conforming to EN/IEC 61800-5-1 IP21 conforming to EN/IEC 60529 IP41 on upper part conforming to EN/IEC 61800-5-1 IP41 on upper part conforming to EN/IEC 60529 IP54 on lower part conforming to EN/IEC 61800-5-1 IP54 on lower part conforming to EN/IEC 60529
Vibration resistance	1.5 mm peak to peak (f= 3...13 Hz) conforming to EN/IEC 60068-2-6 1 gn (f= 13...200 Hz) conforming to EN/IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to EN/IEC 60068-2-27
Noise level	55.6 dB conforming to 86/188/EEC
Relative humidity	5...95 % without condensation conforming to IEC 60068-2-3 5...95 % without dripping water conforming to IEC 60068-2-3
Ambient air temperature for operation	-10...50 °C (without derating)
Operating altitude	<= 1000 m without derating 1000...3000 m with current derating 1 % per 100 m
Operating position	Vertical +/- 10 degree
Product certifications	C-Tick CSA NOM 117 UL GOST
Marking	CE
Standards	EN 55011 class A group 2 EN 61800-3 environments 2 category C3 IEC 60721-3-3 class 3C1 EN 61800-3 environments 1 category C3 EN/IEC 61800-5-1 IEC 60721-3-3 class 3S2 UL Type 1 EN/IEC 61800-3
Assembly style	With heat sink
Electromagnetic compatibility	Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5 Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11
Regulation loop	Adjustable PI regulator
Speed accuracy	+/- 0.01 % of nominal speed in closed-loop mode with encoder feedback 0.2 Tn to Tn +/- 10 % of nominal slip without speed feedback 0.2 Tn to Tn
Ambient air temperature for storage	-25...70 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33.0 cm
Package 1 Width	28.0 cm
Package 1 Length	40.0 cm
Package 1 Weight	9.526 kg
Unit Type of Package 2	S06
Number of Units in Package 2	3
Package 2 Height	73.5 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	41.578 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------