

## SSW 18 LTX 400 BL (602205650) Cordless impact wrench 18V 2x5.2Ah Li-Power; Charger ASC 55 (220-240 V / 50 - 60 Hz); metaBOX 145



Product may differ from Image



- Unique Metabo brushless motor for quick work progress and highest efficiency for any application
- Overload protection: protects the motor from overheating
- High torque accompanied by an exceptionally compact design
- Low kick-back operation with extremely high torque
- Twelve speed/torque levels for a wide range of applications
- Integrated work light for illumination of the work area
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Handy belt hook, can be fixed either on the right or left side
- With metaBOX, the intelligent solution for transport and storage

### Technical data

#### Characteristics

|                             |                             |
|-----------------------------|-----------------------------|
| Type of battery pack        | Li-Power                    |
| Battery voltage             | 18 V                        |
| Battery pack capacity       | 2 x 5.2 Ah                  |
| Max. screw size             | M20                         |
| Max. no-load speed          | 0 - 2150 rpm                |
| Maximum impact rate         | 4250 bpm                    |
| Maximum torque              | 400 Nm / 295 ft. lbs        |
| Max. loosening torque       | 620 Nm / 420 ft. lbs        |
| Speed/torque levels         | 12                          |
| Bit retainer                | Male square 1/2" (12.70 mm) |
| Weight without battery pack | 1.3 kg / 2.9 lbs            |
| Weight with battery pack    | 2 kg / 4.4 lbs              |

#### Vibration

|                              |                      |
|------------------------------|----------------------|
| Impact screwdriving          | 12 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

#### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 100 dB(A) |
| Sound power level (LwA)      | 111 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |