

## PVC WIRE SPRING HOSE



**APPLICATIONS:** Suitable for suction and transfer of water, oil, powder, etc in the industrial, agricultural and marine sector.

**FEATURE:** Light in weight and easy to handle. Good adaptability to hard weather conditions.

**WORKING TEMPERATURE:** -5°C to +65°C

PRODUCT CODE	NOMINAL I.D. (inch)	I.D. (mm)	O.D. (mm)	STANDARD LENGTH (m)	W.P. (bar)	B.P. (bar)
PS012	1/2"	12	18	100	10	30
PS015	5/8"	15	23	100	9	27
PS019	3/4"	19	26	50	9	27
PS025B	1"	25	31	50	5	15
PS025	1"	25	33	50	8	24
PS032B	1-1/4"	32	38	40	4	12
PS032	1-1/4"	32	41	40	7	21
PS038B	1-1/2"	38	45	40	4	12
PS038	1-1/2"	38	48	40	6	18
PS045	1-3/4"	45	56	40	6	17
PS050B	2"	50	58	50	4	12
PS050	2"	50	62	50	6	16
PS065	2-1/2"	64	80	20	5	15
PS075B	3"	75	87	30	3	10
PS075	3"	75	91	30	4	12
PS090	3-1/2"	90	108	20	4	12
PS100	4"	102	120	30	3	10
PS150B	6"	152	167	20	3	9
PS150	6"	152	170	20	3	10