NSYPLM86G

Wall mounted polyester enclosure, Thalassa PLM, plain door, 847x636x300mm, IP66, IK10, RAL 7035





Main

| Range | Thalassa |
|--------------------|----------------------------|
| Product name | Thalassa PLM |
| Device short name | PLM |
| Enclosure type | Multi-purpose |
| Category | Compact enclosure |
| Nominal height | 847 mm |
| Nominal width | 636 mm |
| Nominal depth | 300 mm |
| Enclosure mounting | Wall mounted |
| Device composition | 1 body 1 door 2 lock |
| Door type | Plain |
| Lock type | 3 mm double-bar lock |

Complementary

| Number of locks | 2 |
|-----------------------------|---|
| Mounting plate description | Without mounting plate |
| Accessibility for operation | Front |
| Removable parts | Door by hinges |
| Material | Polyester reinforced with fibreglass |
| Colour | Grey (RAL 7035) |
| Standards | IEC 62208 NEMA classification 4X NEMA classification 13 |
| Product certifications | UL |
| Electrical insulation class | Class II |

Environment

| IP degree of protection | IP66 conforming to IEC 60529 |
|---------------------------------------|--------------------------------|
| IK degree of protection | IK10 conforming to IEC 62262 |
| Fire resistance | 960 °C conforming to IEC 62208 |
| Ambient air temperature for operation | -4080 °C |

Packing Units

| 9 | | |
|------------------------------|-----------|--|
| Unit Type of Package 1 | PCE | |
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 33.000 cm | |
| Package 1 Width | 66.500 cm | |
| Package 1 Length | 92.500 cm | |
| Package 1 Weight | 19.341 kg | |
| | | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|--|--|
| REACh Regulation | ☐ REACh Declaration | |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) | |
| Mercury free | Yes | |
| China RoHS Regulation | China RoHS Declaration | |
| RoHS exemption information | ₫Yes | |
| Environmental Disclosure | Product Environmental Profile | |
| Circularity Profile | No need of specific recycling operations | |