

FEATURES

- A plain copper conductor
- A voltage rating of 600 / 1000 V
- Class 5 flexibility
- A HR PVC (Heat Resistant PVC) insulation

RS PRO Single Core x 6.0sqmm (Class 5 PCW), HRPVC Insulated, 600/1000V, Tri-Rated

RS Stock No.: 811-1476



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

From RS Pro a high quality Tri Rated cable with a 1 m length and colour coding recognised under the European Harmonised designation (HAR) codes H05V2-K and H07V2-K

General Specifications

Type	Tri-rated
Tri-rated	Yes
Sheath Colour	Mid-Blue
Harmonised Code	H05V2-K and H07V2-K
Application	Electrical cabinets, Switch control in power switchgear, Relay and instrumentation panels of power switchgear, Internal connectors in rectifier equipment, Motor starters and controllers, Small electrical devices, Industrial electrical installations, Panel building

Electrical Specifications

Voltage Rating	600/1000V
Current Rating	53A
Conductor Material	78/0.295mm Plain Annealed Copper (Class 5 to IEC 60228)
Insulation Material	HRPVC (Type T13 to BS EN 50363)
Conductor Resistance	3.30 Ω /km @ 20°C (Maximum)

Mechanical Specifications

Length	100m
Cross Sectional Area	6mm ²
Outer Diameter	4.9mm
American Wire Gauge	10
Core Strands	78/0.295mm
Size of Strands	0.295mm
Insulation Wall Thickness	0.8mm
Minimum Bend Radius	6 x Overall Diameter
Weight	71kg/km
Diameter Over Insulation	Lower Limit: 4.40mm; Upper Limit: 5.30mm

Operation Environment Specifications

Maximum Operating Temperature	90°C
Maximum Conductor Temperature	105°C in air; 60°C in oil
Temperature Range	-15 to +105°C

Approvals

Compliance/Certifications	UL & CSA
Standards Met	UL 1015 & CSA Type TEW & BS 6231 Type CK

AWM Size	Area mm ²	Wire Type	UL Style	Nominal R/T (mm)	Nominal Diam (mm)	Current Rating (A)	Weight Kg/Km
22	0.5	16/0.2	1015	0.80	2.6	11	1
20	0.75	24/0.2	1015	0.80	2.8	14	14
18	1.0	32/0.2	1015	0.80	3.0	17	17
16	1.5	30/0.25	1015	0.80	3.3	21	22
14	2.5	50/0.25	1015	0.80	3.7	30	33
12	4.0	56/0.3	1015	0.80	4.3	41	49
10	6.0	78/0.295	1015	0.80	4.9	53	71
8	10	80/0.4	1028	1.20	6.8	75	124
6	16	126/0.4	1283	1.58	9.2	100	199
4	25	196/0.4	1283	1.58	10.6	136	290
2	35	276/0.4	1283	1.58	11.6	167	387
1	50	396/0.4	1284	2.10	14.4	190	570
2/0	70	360/0.5	1284	2.10	16.5	240	781
3/0	95	475/0.5	1284	2.10	18.7	300	1025
4/0	120	608/0.5	1284	2.10	20.0	340	1280

