

FEATURES

- Front hinged, low profile switch
- Raised tread pattern
- Foot or palm operation
- Momentary (non-latching) action with SPDT contacts
- Supplied with 2m of cable
- Dual version - 2 N/O contacts with a common connection
- Operating temperature: -5°C to 40°C

RS PRO General Purpose Momentary Foot Switch - Thermoplastic Case Material, SP-CO, 3 A Contact Current, 250V Contact

RS Stock No.: 218-4245



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description ATTRIBUTE 1

RS PRO foot switches which are ideal for a number of applications. The low profile switch is designed for improved user comfort and is constructed from plastic with a raised tread pattern

This range of foot pedal switches includes:

218-4245 – Momentary, Single Pole Double Throw (SPDT)

218-4267 – Momentary, Single Pole Double Throw (SPDT)

251-2224 - Momentary, Single Pole Double Throw (SPDT), Yellow cover and black base

325-2692 - Momentary, Single Pole Double Throw (SPDT), Green cover and black base

325-2686 - Momentary, Single Pole Double Throw (SPDT), Red cover and black base

325-2715 – Momentary, 2 NO

513-5145 – Momentary, 2 X SPST, medically approved

General Specifications

Contact Configuration	SP-CO
Switch Operation	Momentary
Case Material	Thermoplastic
Switch Environment	General Purpose
Contact Material	Silver
Colour	Black, Grey
Applications	Foot switches are commonly used in applications where hands-free control is more practical or safer. They can be found on: Industrial machinery and smaller power tools, Hospital beds, Dentist Chairs, Lamps

Electrical Specifications

Contact Voltage Rating (AC)	250V
Contact Voltage Rating (DC)	24V
Contact Current Rating	3A

Mechanical Specifications

Length	90mm
Height	27mm
Dimensions	90mm x 65mm x 27mm
Width	65mm

Operation Environment Specifications

Operating Temperature	-5 to 40°C
------------------------------	------------

Protection Category

IP Rating	IPX2
------------------	------

Approvals

Standards Met	2014/35/EU, EN 60950
Compliance/Certifications	EN 61058-2-1; EN 61058; EN 60601-1; EN 60950, RoHS



Outline Dimensions

