

Eaton RES-40

Catalog Number: RES-40

Eaton Bussmann series RES fuse, time lag, non current-limiting, Industrial and commercial structures, 40 A, Class H, Non-indicating, Ferrule end x ferrule end, 10 kAIC at 250 Vac, Standard, 10, 600 V

General specifications



Product Name	Catalog Number
Eaton Bussmann series RES fuse	RES-40
UPC	EAN
051712110402	5027590243995
Product Length/Depth	Product Height
0.78 in	5.5 in
Product Width	Product Weight
0.78 in	0.29 lb
Warranty	Compliances
Not Applicable	RoHS Compliant

Product specifications

Fuse indicator

Non-indicating

Special features

Super lag, time lag, non current-limiting

Interrupt rating

10 kAIC at 250 Vac

Type

Renewable fuse

Connection

Ferrule end x ferrule end

Quantity

10

Class

Class H

Voltage rating

600 V

Application

Industrial and commercial structures

Amperage Rating

40 A

Packaging type

Standard

Resources

Catalogs

[RES-40-SUPER LAG RENEWABLE FUSE 40/600](#)

[Bussmann series complete full line catalog no. 1007](#)

Multimedia

[Bussmann series Fuseology](#)

Specifications and datasheets

[Eaton Specification Sheet - RES-40](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](#)