



Type	S.N
J	621-2344
K	621-2287

0	Creation	BLONDEL N.	11.05.2006	DP
Ind.	Object	Drawn :	Date :	Checked : Date :
TYPE J/K SELF ADHESIVE PTFE 1M E06069-E06070		N° CF TABLE		
		Material :	Scale :	
		-	N.T.S	
		unless otherwise specified Generale tolerances: ± 0.1 mm		
94-05-08-TE-079 Rév.2				

Type	S.N
J	621-2344
K	621-2287

3	Sleeve	PE
2	Cable	PTFE Twisted
1	Patch	COPPER
<b>Tag</b>	<b>Description</b>	<b>Material</b>


0	Creation	BLONDEL N.	11.05.2006	DP	11.05.2006
Ind.	Object	Drawn :	Date :	Checked :	Date :

TYPE J/K SELF ADHESIVE PTFE 1 M E06069-E06070	<b>N° CF TABLE</b>
--	--------------------

	Material : -	Scale : N.T.S
	<small>unless otherwise specified Generale tolerances: ± 0.1 mm</small>	

**Description**

Self adhesive

**Thermocouple type**

J	621-2344
K	621-2287

**Grounded or Ungrounded**

Grounded

According to IEC-BS 4937 60584-2 & IEC-BS 4937 60584-3

**RoHS compliance**

Yes

**Accuracy Class 1**

±1.5°C or ±0.004xT

**Colour Codes IEC 60584**

Type	J	K
+VE arm	black	green
-VE arm	white	white
Overall	black	green
T* Range	-50 to +750*	-50 to 1100*
Operating T*	0 to +200	0 to +200

**Cable characteristics**

Solid Wire Section and Diameter  
Conductor Insulation  
Length

0.03 mm<sup>2</sup> / 0.2 mm  
PTFE Twisted  
1000 mm

**Patch dimensions**

ø 6.35 mm

**Connection**

by kapton self adhesive

**Application**

Surface Temperature

0	Creation	BLONDEL N.	11.05.06	DP	11.05.06
Ind.	Object	Drawn :	Date :	Checked :	Date :

**TYPE J / K SELF ADHESIVE  
E06069/E06070**

**N° CF TABLE**



Material :

Scale :

N.T.S

Unless otherwise specified generales tolerances ± 0,1mm



94-05-08-TE-079 Rév.2