Screened Twisted Pair Computer Security and Instrumentation Cable





RoHS Compliant

Application

The cable is suitable for instrumentation, computer and security applications, point of sale, control systems, and RS232 applications.

Construction

Conductor : 2 -Twisted-Pairs, Class 2 stranded tinned copper conductors

Insulation : PE (Polyethylene)
Screen : Aluminium foil tape
Drain Wire : Stranded tinned copper
Sheath : PE (Polyethylene)

Characteristics

Voltage Rating : 300V

Temperature Rating : Fixed : -20°C to +80°C Core Identification : Pair 1 : Black & Red

Pair 2 : Green & White

Sheath Colour : Black

Electrical Characteristics

Nominal Characteristic Impedance	Capacitance at 1kHz pF/m	Max. Resistance of Conductor at 20°C Ω /km	
52Ω	114.8	65.3	

Dimensions

No. of Pairs	AWG Size	Conductor Area CSA mm²	No. of Max. Strands × Strand Size (Ø mm)	Nominal Overall Diameter mm	Nominal Weight kg/km
2	22	33	7 × 0.24	5.8	30

Part Number Table

Description	Reel Length (m)	Part Number
Screened Twisted Pair Cable, 2 PR, 22AWG, PE	50	PP000867

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



Page <1> 30/08/22 V1.1