



Type	S.N
J	621-2142
K	621-2158
N	621-2136
T	621-2164

0	Creation	BLONDEL N.	11.05.2006	DP	11.05.2006
Ind.	Object	Drawn :	Date :	Checked :	Date :
TYPE x WELDED TIP PTFE 1M E06061-E06062-E06063-E06064		N° CF TABLE			
		Material :	Scale :		
		-	N.T.S		
		<small>unless otherwise specified Generale tolerances: ± 0.1 mm</small>			
<small>94-05-08-TE-079 Rév.2</small>					

Type	S.N
J	621-2142
K	621-2158
N	621-2136
T	621-2164

2	Sleeve	PE
1	Cable	PTFE Twisted
Tag	Description	Material

0	Creation	BLONDEL N.	12.05.2006	DP	12.05.2006
Ind.	Object	Drawn :	Date :	Checked :	Date :

TYPE x WELDED TIP PTFE 1M E06061-E06062-E06063-E06064	N° CF TABLE
--	-------------

	Material : -	Scale : N.T.S
	<small>unless otherwise specified Generale tolerances ± 0.1 mm</small>	

Description

Welded tip

Thermocouple type

J	621-2142
K	621-2158
N	621-2136
T	621-2164

Grounded or Ungrounded

Grounded

According to IEC-BS 4937 60584-2 & IEC-BS 4937 60584-3

RoHS compliance

Yes

Accuracy Class 1

±1.5°C

Type T ±0.5°C up to 125°C
but after ±0.004xT°C

Colour Codes IEC 60584

Type	J	K	N	T
+VE arm	black	green	pink	brown
-VE arm	white	white	white	white
Overall	black	green	pink	brown
T° Range	-50 to +750°	-50 to 1100°	up to 1200°	-200 to +350°
Operating T°	-50 to +260	-50 to +260	-50 to +260	-50 to +260

Cable characteristics

Solid Wire Section and Diameter
Conductor Insulation
Length

0.03 mm² / 0.2 mm
PTFE Twisted
1000 mm

Application

All using in accordance with operating temperature

0	Creation	BLONDEL N.	11.05.06	DP	11.05.06
Ind.	Object	Drawn :	Date :	Checked :	Date :

**TYPE J/K/N/T WELDED TIP PTFE 1M
E06061/E06062/E06063/E06064**

N° CF TABLE



Material :

Scale :

N.T.S

Unless otherwise specified generales tolerances ± 0,1mm



94-05-08-TE-079 Rév.2