S56C313RCD30GY

RCD Protected socket - 13A 240V - 3 phase 3 pole - flat pin - grey



Main

Mani	
Range	WPS
Device short name	56 series
Product or component type	Residual current device switch
Colour tint	Light grey

Complementary

Control type	Push-button
Material	PVC (polyvinyl chloride) UV stabilised
Surface finish	Gloss
Installation direction	Vertical
Width	101 mm
Height	203 mm
Rated current	13 A
[Ue] rated operational voltage	240/250 V
Network frequency	50 Hz
Network number of phases	3 phases
Number of gangs	2 gangs
Pin number	3
Device composition	Flat pin
Mounting mode	Surface mounted

Environment

IP degree of protection	IP66

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	11.5 cm	
Package 1 Width	10.4 cm	
Package 1 Length	20.8 cm	
Package 1 Weight	1.25 kg	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins