

Datasheet

RS Pro Stainless Steel Countersunk Head Machine Screws, M5 x 25mm

RS Stock No: **914-1951**



Product Details

RS Pro machine screw measuring M5 x 25 mm, is made of type 316 S16 A4 grade 18//8 stainless steel, which has higher level of corrosion resistance than A2 stainless steel. The countersunk head screw can be used at up to 300°C. The cross drive screw is suitable for use in food, medical, chemical, construction and electronic applications. This machine screw meets DIN965 standards.

Features and Benefits

- To DIN965
- A4 grade 18/8 stainless steel (Type 316 S16) construction
- Higher level of corrosion resistance than A2 S/S
- Suitable for use up to 300°C
- Suitable for use in most food, medical, chemical, construction and electronic applications

**Specifications:**

| | |
|----------------------|-----------------|
| Drive Type | Pozidriv |
| Finish | Plain |
| Head Shape | Countersunk |
| Material | Stainless Steel |
| Length | 25 mm |
| Stainless Steel Type | 316 (A4) |
| Thread Pitch | 0.8 |
| Thread Size (Metric) | M5 |
| Head Diameter | 8.94 to 9.3 mm |
| Head Height | 2.7 mm |
| Recess Diameter | 2.6 to 3.05 mm |
| Specification | DIN 965 |