



Main

Range	Actassi
Product brand	Schneider Electric
Product type	Keystone modular jack
Provided equipment	Without shutter
Colour tint	Metal (zamak)
Wiring Colour configuration	TIA-568A/B
Type of packing	Plastic bag and carton
Quantity per set	Set of 1

Complementary

[In] rated current	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts
Contact resistance	20 mOhm
Insulation resistance	>= 500 MOhm
Connector type	RJ45
Tool type	Punch down tool Quick termination tool
Cable outer diameter	0.9...1.4 mm
Compatible LAN cable types	STP
Communication network category	6 _A
Supported applications	10GBASE-T
Product compatibility	RJ45 plug
Type of footprint	S-110 keystone
Targeted region	Asia Pacific.

Environment

Operational temperature range	-10...60 °C
Ambient air temperature for storage	-20...70 °C
Relative humidity	0...93 %
Climatic category	40/070/21 (21 days)
Flame retardance	UL94-V0 conforming to UL listed
Product certifications	FCC part 68 F[RETURN]IEC 60603-7
Standards	ISO/IEC 11081 IEC 60603-7 ANSI/TIA/EIA-568-B

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.4 cm
Package 1 Width	4.8 cm
Package 1 Length	48.2 cm
Package 1 Weight	40.0 g

Unit Type of Package 2	CAR
Number of Units in Package 2	160
Package 2 Height	27.0 cm
Package 2 Width	32.0 cm
Package 2 Length	38.0 cm
Package 2 Weight	7.104 kg
Unit Type of Package 3	P12
Number of Units in Package 3	2880
Package 3 Height	95.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	127.872 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------