



# Supermask Masking Tape

## 1. Product description

High performance masking tape provided with cured rubber-based adhesive coated on crepe paper.

## 2. Main Application

suitable for automobile painting, indoor painting and splicing.

## 3. Features

Clean removal on most commercial and household surfaces.

## 4. Physical properties

Item	Unit	Specification	Test methods
Total Thickness	Micron ( $\mu$ )	$140 \pm 15$	PSTC – 133
Adhesion to steel	Kg / 25mm	$0.8 \pm 0.1$	PSTC - 101
Tensile strength	Kg / 25mm	$8 \pm 2$	PSTC – 131
Elongation at break	%	$13 \pm 5$	PSTC - 131
Max temp. Resistance	°C	95/30 minutes	-

## 5. Notes

1. Tapes must be stored in its original packaging in a cool, dry area away from direct sunlight exposure and from freezing. Storage temperature should be as close as possible to room temperature. Suggested storage temperature should range from 15~30°C with max humidity of 60%
2. Surfaces to which tape is applied should be clean, dry and free of dust, grease, oil or other contaminants.
3. Recommended application condition 10 ~40°C
4. With a storage temperature lower than 10°C, it is always suggested temperature reconditioning of the tape at room temperature (15 ~ 30°C) before its use.
5. Shelf life 12 months for slit rolls and 6 months for jumbo rolls from date of manufacture
6. The values stated in this document are only test values, not guaranteed values