

USB to VGA Adapter - External USB Video Graphics Card for PC and MAC- 1920x1200

Product ID: USB2VGAPRO2



The USB2VGAPRO2 USB to VGA Adapter functions as an external graphics card for Windows® and Mac® computers - the perfect solution for turning your desktop or laptop computer into a dual or multi-monitor environment, all through the simplicity and convenience of USB.

The USB-VGA Adapter delivers high quality video (up to 1920x1200) for a variety of applications and is capable of simultaneously running up to five additional displays from a single computer (using four USB2VGAPRO2 External Video Adapters). The adapter connects to a host computer through a USB 2.0 port, acting as an external VGA video card to either extend or mirror the desktop shown on the existing display - without having to open the computer case.

Featuring driver support for Microsoft Windows® (including Aero themes) and Mac OS X, and with video support for resolutions up to 1920x1200, this USB-VGA video adapter is the ideal solution for a wide rade of operating environments as well as large-screen displays/monitors.

The USB2VGAPRO2 USB to VGA Adapter is backed by a StarTech.com 2-year warranty and free lifetime technical support.



Data Sheet

Certifications, rapports et compatibilité













Applications

- Add multiple (up to five) monitors / projectors to your computer setup using one USB2VGAPRO2 device for each additional display
- View large or multiple spreadsheets across multiple displays
- Increase productivity by running multiple applications on different VGA screens; check your email on one display while editing a document on the other
- Use the USB-VGA adapter to connect your PC to your television for showing family pictures and movies
- Connect multiple VGA monitors to a single computer to create engaging multimedia presentations
- Great for researchers and writers offering the ability to have reference material on one display and a working document copy on the other

Spécifications techniques

- Optimal performance at 1920x1200 and ideal for use with 24" to 26" monitors or smaller
- Support for Aero themes in Windows $\ensuremath{\mathbb{R}}$
- Works with Mac® OS X
- Connect up to five adapters to one PC for a true extended desktop experience
- USB-Powered operation, no external power adapter required
- Quick and easy installation
- Powered by DisplayLink DL-195 chip



Hardware

Performance

Hard-to-fine

| d made easy* | Data Sheet |
|----------------------------|--|
| Warranty | 2 Years |
| AV Input | USB 2.0 |
| AV Output | VGA |
| Chipset ID | DisplayLink - DL-195 |
| Memory | 16MB |
| USB Pass-Through | No |
| General Specifications | This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a Trigger or Fresco family chipset. |
| Maximum Analog Resolutions | 1920x1200 (32-bit Color) |
| MTBF | 87,703 hours |
| Supported Resolutions | Standard(16/32 bit): 640x480, 800x600, 1024x768, 1280x1024, 1600x1200 |
| | Widescreen(16/32 bit): |

| | | Widescreen(16/32 bit): 1366x768, 1440X900, 1680x1050, 1920x1200 |
|---------------|-------------------------------|---|
| Connector(s) | Connector Type(s) | 1 - USB Type-A (4 pin) USB 2.0 Male |
| | | 1 - VGA (15 pin, High Density D-Sub) Female |
| Software | OS Compatibility | Windows® 2000, XP, Vista, 7, 8, 8.1, 10 MacOS® 10.6 to 10.13.3 Chrome OS v51 Ubuntu 14.04, 16.04 |
| Requirements | Note | Power PC-based Macintosh computers, such as late-model iMacs, PowerBooks and PowerMacs, are not currently supported |
| | | Extended displays are currently only supported with DisplayLink-based products on macOS 10.11 to 10.13.3. This may change in future versions. |
| | System and Cable Requirements | 1.2Ghz or higher CPU 30MB of hard drive space 512 MB RAM USB 2.0 Port Not intended for gaming |
| Indicators | LED Indicators | 1 - Blue - Power |
| Power | Power Source | USB-Powered |
| Environmental | Humidity | <85% non-condensing |
| | Operating Temperature | 10°C to 40°C (50°F to 104°F) |



Data Sheet

| Storage Temperature | -10°C to 80°C (14°F to 176°F) |
|---------------------------|---|
| Cable Length | 6.5 in [165 mm] |
| Color | Black |
| Product Height | 0.6 in [15.5 mm] |
| Product Length | 3.1 in [78 mm] |
| Product Weight | 10.6 oz [300 g] |
| Product Width | 1.7 in [43.5 mm] |
| Shipping (Package) Weight | 8.5 oz [240 g] |
| Included in Package | 1 - USB to VGA Adapter |
| | 1 - Driver CD |
| | 1 - Instruction Manual |
| | Cable Length Color Product Height Product Length Product Weight Product Width Shipping (Package) Weight |

L'apparence et les spécifications du produit peuvent être modifiées sans préavis