

## **Features**

- Capacity: 10 Ton
- Stroke: 355 mm
- Fast spring return, designed to work in any position.
- Threads on body, plunger and base holes for its fixation.
- With chrome-plated plunger and scraper to extend cylinder life.
- Standard plain saddle. Optional tilting saddle.

# **RS PRO Hydraulic Cylinders**

RS Stock No.: 2358234



RS PRO Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



#### **Product Description**

Cylinders for general industrial applications. The single acting hydraulic cylinders have only one female quick coupler. If the coupler has to be installed on the cylinder, apply Teflon around the 3/8" NPT male thread of the coupler.

#### **General Specifications**

Cylinder Part Number	2358234
Stock Code	2358234
Cylinder Type	Steel, Solid Plunger, Spring Return
Single/Double Acting	Single Acting
Capacity	10 Ton
Stroke	355 mm
Cylinder Effective Area	16 cm <sup>2</sup>
Oil Capacity	565 cm <sup>2</sup>
Body Material	Steel
Saddle Type	Standard Plain
Handles	No
Applications	General industrial use



#### **Mechanical Specifications**

r	I
Maximum Operating Pressure	700 bar - 10150 psi
Closed Height	454 mm
Extended Height	809 mm
Cylinder Base to Advance Port	20 mm
Saddle Protrusion from Plunger	6 mm
Collar Thread	2 1/4"-14 un
Collar Thread Length	32 mm
Weight	8.4 kg
Plunger Thread	1"-8 un
Plunger Thread Length	19 mm
Base Hole Thread	5/16"-18 un
Base Hole Thread Length	12 mm

Diameters:	
Outside Diameter	60 mm
Cylinder Bore	45 mm
Plunger	36 mm
Saddle	28 mm
Bolt Circle	39 mm

### **Approvals**

Compliance/Standards	CE, UKCA

