

FEATURES

- Aerogel microporous thermal insulation sheet
- Length of 1 m
- Width of 700 mm
- Maximum operating temperature of +650°C
- Density of 0.18 g/cc
- Low thermal conductivity
- Low thickness (10 mm) and profile
- Environmentally safe
- Hydrophobic (repels liquid)
- Prevents corrosion

Aerogel Miroporous Blanket Thermal Insulation, 1m x 700mm x 10mm

RS Stock No.: 103-4078



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

When you need a thermal insulation sheet that offers improved performance with a reduced thickness, turn to this aerogel microporous blanket. Silica aerogels have the lowest thermal conductivity of any known solid. This means they provide reliable insulation with a lower thickness than similar products made from other materials.

The sheet is silica-aerogel reinforced with non-woven glass fibre batting and is ideal for insulating everything from pipes to vessels and tanks. It's also hydrophobic – meaning it repels liquid – which helps prevent corrosion under the insulation and is environmentally safe.

General Specifications

| | |
|---------------------------------|--|
| Material | Aerogel Miroporous Blanket |
| Flame Retardant | Yes |
| Thermal Shock Resistance | Yes |
| Application | Thermal insulation, heat shields, heat containment, gaskets and expansion joints in industrial furnaces, ovens, kilns, boilers and other process equipment |

Mechanical Specifications

| | |
|------------------|-----------------------|
| Length | 1m |
| Width | 700mm |
| Thickness | 10mm |
| Density | 0.18g/cm ³ |

Operation Environment Specifications

| | |
|--------------------------------------|--------|
| Maximum Operating Temperature | +650°C |
|--------------------------------------|--------|

Approvals

| Compliance/Certifications | |
|---------------------------|--|
|---------------------------|--|

| | |
|--|---------|
| | EN61340 |
|--|---------|