

FEATURES

- Wire is unterminated and partially stripped
- Cable
 length is 2m
- Insulation Resistance >= 100 MΩ
- Brass nickel plated coupling nut

RS PRO M12 MALE RIGHT ANGLE CONNECTOR ASSEMBLY 8 PIN 8 WIRE 2m PUR CABLE

RS Stock No.: 2067634



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description ATTRIBUTE 1

M12 Single Ended Cable Assembly

Brought to you under the trusted RS Brand, this range of M12 connector cable assemblies are commonly used in sensor and automation equipment. Boasting a high degree of environmental protection, they are ideal for industrial use. Fitted with a secure coupling nut, these RS M12 Connector Cable Assemblies are left un-terminated and partially stripped at one end, and are an ideal solution for when secure and reliable data transference is needed.

Features and Benefits:

- · Wire is un-terminated and partially stripped
- Insulation Resistance >= 100 MΩ
- Brass nickel plated coupling nut

General Specifications

Rated Operational Voltage	30 V
Current Rating	2A
Insulation Resistance	>= 100 MΩ
Temperature Range	-25°C +75°C
Coding	A-Coded

Material Specifications

Grip Material	PU
Contact	Cu-Zn
Contact Plating	Gold Flash
Contact Carrier	Nylon 66
Grip Color	Black
Coupling Nut	Brass Nickel-Plated

Cable Specifications

Cable Length-L	2 m
Cable Type	8 Core PUR Multi Strand
Sheath Color	Black

RS PRO M12 SINGLE ENDED CABLE ASSEMBLY




Cross Section of Wire	0.25 sq. mm
Core Dia	1.3 mm
Cable Dia	6.8 ± 0.1 mm
Termination	Partially Stripped


Protection Category	
Degree of Protection	IP67
Additional Information	
Custom Tariff Number	85369090
Approvals	
Standards Met	IEC 61076-2-101

Similar Products

Stock No.	Brand	Product Name	Attribute 1	Attribute 2

Connection Diagrams / Assembly Diagrams / Illustrations / Accessories







All Dimensions are in mm.