



Main

Range of product	Acti 9
Product or component type	Fault contact
Device short name	ISD
Signal contacts composition	1 C/O
[In] rated current	1 A: 130 V DC 1.5 A: 60 V DC 2 A: 48 V DC 6 A: 24 V DC 3 A: 415 V AC - 50/60 Hz 6 A: 240 V AC - 50/60 Hz
9 mm pitches	1

Complementary

Range compatibility	Acti 9 iC60 Acti 9 iC65 Acti 9 iC60 RCBO Acti 9 iID Acti 9 ARA Acti 9 RCA Acti 9 iDPN (China version) Acti 9 iDPN Vigi Acti 9 iC40 Acti 9 iSW-NA
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Local signalling	Mechanical indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Height	86 mm
Width	9 mm
Depth	73 mm
Net weight	33 g

Colour	White
Connections - terminals	Screw clamp terminal2 cable(s) 2.5 mm ² - rigid Screw clamp terminal2 cable(s) 1.5 mm ² - flexible with ferrule Screw clamp terminal1 cable(s) 0.5...2.5 mm ² - flexible Screw clamp terminal1 cable(s) 1...4 mm ² - rigid
Wire stripping length	10 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Package 1 Weight	46.000 g
Package 1 Height	0.780 dm
Package 1 width	0.200 dm
Package 1 Length	0.925 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------