

**LPS 2®**

Heavy-Duty Lubricant



FEATURES

- Strong, multi-purpose lubricant and penetrant with added corrosion protection
- Provides a non-drying, light, oily film
- Reduces wear caused by friction and corrosion
- Loosens rusted or frozen parts
- Provides superior corrosion protection of metal parts during shipment
- Protects metal parts during indoor storage up to one year
- Does not contain silicone
- Displaces moisture
- Safe to use on most plastics, rubbers and paint
- Contoured can for improved hand grip

APPLICATIONS

- Bearings & valves
- Cables & linkages
- Hand tools
- Add Dies, bits & fasteners
- Slides & tracks
- Productions & transportation equipment
- Metal parts in storage
- Pulleys & rollers
- Engines & electric motors

SPECIFICATIONS AND APPROVALS

- A-A-50493D, Class B, Type II (aerosol)
- A-A-50493D, Class B, Type I (bulk)
- Caterpillar 1E4970
- Ford Motor Co.
- MIL-PRF-16173E Grade 3 Class 1 (except 3.5, 3.6)
- NSF International, H2 (aerosol)
- NSF International, H2 (bulk)
- Pratt & Whitney Canada MMC 21530

PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Brown
Odor	Slight petroleum odor. Cherry.
Melting / Freezing Point	<-58°F (< -50°C)
Boiling Point / Range	383°F (195°C) @ 101kPa
Flash Point	174.2°F (79.0°C) Tag Closed Cup (dispensed liquid)
Evaporation Rate	<0.1 BuAc
Flammability	Lower: 0.6%, Upper: 7%
Vapor Pressure	<0.05 mmHg @ 20°C (dispensed liquid)
Vapor density	4.7 (air=1)
Partition Coefficient	<1
Auto-Ignition Temperature	>442.4°F (>228°C)
Viscosity	<7 cSt @ 25°C
Percent volatile	92-95%
Specific Gravity	0.82-0.86 @ 20°C
VOC Content	0% per U.S. State and Federal Consumer Product Regulations
Temperature Range	-58°F to 350°F
Dielectric Strength	33kV
Propellant	CO2

DIRECTIONS

Shake well before using. Spray on clean surfaces. Use the attached extension tube for pinpoint application. Safe to use on plastic, rubber, and painted surfaces.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

See section 13 of the SDS.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Europe				
	M00215	5 L	pail	1	
	M00205	20 L	pail	1	
00216	M00216	11 wt oz / 312 g / 369 mL	aerosol	12	12 lbs
00222		20 fl oz / 591 mL	trigger	12	18 lbs
02128		1 gal / 3.78 L	can	4	34 lbs
00205		5 gal / 18.93 L	pail	1	39 lbs
00255	M00255	55 gal / 208 L	drum	1	400 lbs