

FEATURES

- WATERTIGHT
- INDESTRUCTIBLE
- FOR PROFESSIONAL USE
- PROTECTIVE
- MILITARY GRADE
- WITH PRE-CUBED FOAM
- STACKABLE

RS PRO Flight Cases & Equipment Cases

RS Stock No.: 2537423, 2537424, 2537426, 2537427, 2537428, 2537429, 2537430, 2537431, 2537432, 2537433, 2537434, 2537435, 2537436, 2537437, 2537438, 2537439



Airtight containers, resistant to chemicals, moisture and dust. Resistant to the most extreme temperatures (-33 ° C / + 90 ° C).

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

WATERPROOF CASE IN COPOLYMER POLYPROPYLENE

Indestructible cases recommended for professional use.

REMOVABLE LID WITH SAFETY LOCK

To remove the cover, simply tilt it at 70 ° after releasing the screws on the hinges rear

REINFORCED HINGES WITH ANTI CORROSION METAL PIN

STURDY CLOSURES

SEALING O-RING AND AUTOMATIC PRESSURE RELEASE VALVE


ID REMOVABLE PLATE

ANTI TILT SUPPORTS (in some models)

WITH PRECUBED FOAM INSIDE


General Specifications

METRIC MM-KG-C°



INTERNAL DIMENSIONS		EXTERNAL DIMENSIONS		OTHER DATA	
L LENGTH	420 mm	L LENGTH	457 mm	WEIGHT EMPTY	2.4 Kg
W WIDTH	300 mm	W WIDTH	367 mm	WEIGHT WITH FOAM	3 Kg
D DEPTH	160 mm	D DEPTH	183 mm	WEIGHT WITH CUSTOM FOAM	Kg
LID	35 mm			VOLUME	20 lt
BASE	125 mm			BUOYANCY	14.2 Kg/max
				OPERATING TEMPERATURE	°C min -33 / max +90

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS		EXTERNAL DIMENSIONS		OTHER DATA	
L LENGTH	16 9/16 in	L LENGTH	18 in	WEIGHT EMPTY	5.29 lbs
W WIDTH	11 13/16 in	W WIDTH	14 7/16 in	WEIGHT WITH FOAM	6.61 lbs
D DEPTH	6 5/16 in	D DEPTH	7 3/16 in	WEIGHT WITH CUSTOM FOAM	lbs
LID	1 3/8 in			VOLUME	5.28 gal
BASE	4 15/16 in			BUOYANCY	31.30 lbs/max
				OPERATING TEMPERATURE	°F min -27.4 / max +194